

# Contents

<b>Preface</b>	<b>xiii</b>
<b>List of Acronyms</b>	<b>xv</b>
<b>1 Related Work and Preliminary Considerations</b>	<b>1</b>
1.1 Introduction . . . . .	1
1.2 Related Work . . . . .	2
1.2.1 A Routing-Based Approach . . . . .	2
1.2.2 An Information-Theoretic Approach . . . . .	3
1.2.3 A Dynamic Control Approach . . . . .	4
1.2.4 A Game-Theoretic Approach . . . . .	4
1.3 A New Perspective for the Design of Ad Hoc Wireless Networks . . . . .	5
1.4 Overview of the Underlying Assumptions in the Following Chapters . . . . .	9
1.5 The Main Philosophy Behind the Book . . . . .	11
<b>2 A Communication-Theoretic Framework for Multi-hop Ad Hoc Wireless Networks: Ideal Scenario</b>	<b>15</b>
2.1 Introduction . . . . .	15
2.2 Preliminaries . . . . .	16
2.2.1 Topology . . . . .	16
2.2.2 Route Discovery . . . . .	17
2.2.3 Average Number of Hops . . . . .	18
2.3 Communication-Theoretic Basics . . . . .	18
2.3.1 Bit Error Rate at the End of a Multi-hop Route . . . . .	18
2.3.2 Link Signal-to-Noise Ratio . . . . .	20
2.4 BER Performance Analysis . . . . .	23
2.4.1 Uncoded Transmission . . . . .	23
2.4.2 Coded Transmission . . . . .	27
2.5 Network Behavior . . . . .	29
2.5.1 Minimum Spatial Energy Density and Minimum Transmit Power for Full Connectivity . . . . .	30
2.5.2 Connectivity: Average Sustainable Number of Hops . . . . .	34
2.5.3 Lifetime of a Node . . . . .	40
2.6 Concluding Remarks . . . . .	41

<b>3</b>	<b>A Communication-Theoretic Framework for Multi-hop Ad Hoc Wireless Networks: Realistic Scenario</b>	<b>43</b>
3.1	Introduction . . . . .	43
3.2	Preliminaries . . . . .	44
3.3	Communication-Theoretic Basics . . . . .	46
3.4	Inter-node Interference . . . . .	48
3.4.1	Geometric Considerations . . . . .	48
3.4.2	Traffic Model . . . . .	49
3.5	RESGO MAC Protocol . . . . .	50
3.5.1	Scenario with Strong LOS and Interference from Nodes in Tier 1 . . . . .	50
3.5.2	Scenario with Strong LOS and Interference from Nodes in Tiers 1 and 2 . . . . .	57
3.5.3	Scenario with Strong Multipath (Rayleigh Fading) . . . . .	58
3.5.4	Discussion . . . . .	63
3.6	RESLIGO MAC Protocol . . . . .	64
3.6.1	Scenario with Strong LOS . . . . .	66
3.6.2	Scenario with Strong Multipath (Rayleigh Fading) . . . . .	69
3.6.3	Discussion . . . . .	72
3.7	Network Behavior . . . . .	73
3.7.1	Minimum Spatial Energy Density and Minimum Transmit Power for Full Connectivity . . . . .	73
3.7.2	Scenario with Strong LOS . . . . .	73
3.7.3	Scenario with Strong Multipath (Rayleigh Fading) . . . . .	75
3.7.4	Connectivity: Average Sustainable Number of Hops . . . . .	78
3.8	Conclusions . . . . .	83
<b>4</b>	<b>Connectivity in Ad Hoc Wireless Networks: A Physical Layer Perspective</b>	<b>85</b>
4.1	Introduction . . . . .	85
4.2	Quasi-regular Topology . . . . .	86
4.2.1	A Formal Definition of Quasi-regular Topology . . . . .	87
4.2.2	A Communication-Theoretic Approach . . . . .	88
4.2.3	What Happens if Each Node has Two Spatial Neighbors? . . . . .	93
4.2.4	What Happens if There is Inter-node Interference? . . . . .	96
4.3	Random Topology . . . . .	100
4.3.1	Related Work . . . . .	100
4.3.2	Connectivity in Ad Hoc Wireless Networks with Random Topology . . . . .	102
4.3.3	Evaluation of the Likelihood of Broadcast Percolation . . . . .	104
4.3.4	What Happens if There is Inter-node Interference? . . . . .	108
4.4	Concluding Remarks and Discussion . . . . .	109
<b>5</b>	<b>Effective Transport Capacity in Ad Hoc Wireless Networks</b>	<b>111</b>
5.1	Introduction . . . . .	111
5.2	Model and Assumptions . . . . .	113
5.3	Preliminaries . . . . .	115
5.3.1	Route Bit Error Rate . . . . .	115
5.3.2	Link Signal-to-Noise Ratio . . . . .	115
5.3.3	Average Sustainable Number of Hops . . . . .	117
5.4	Single-Route Effective Transport Capacity . . . . .	117

5.5	Aggregate Effective Transport Capacity . . . . .	120
5.5.1	Ideal (no INI) Case . . . . .	121
5.5.2	Realistic (INI) Case: RESGO MAC Protocol . . . . .	123
5.5.3	Realistic (INI) Case: RESLIGO MAC Protocol . . . . .	128
5.6	Comparison of the RESGO and RESLIGO MAC Protocols . . . . .	131
5.7	Spread-RESGO: Improved RESGO MAC Protocol with Per-route Spreading Codes . . . . .	134
5.8	Discussion . . . . .	138
5.9	Concluding Remarks . . . . .	141
<b>6</b>	<b>Impact of Mobility on the Performance of Multi-hop Ad Hoc Wireless Networks</b> . . . . .	<b>143</b>
6.1	Introduction . . . . .	143
6.2	Preliminaries . . . . .	144
6.2.1	Ideal (no INI) Case . . . . .	147
6.2.2	Realistic (INI) Case . . . . .	147
6.3	Switching Models . . . . .	149
6.3.1	Opportunistic Non-reservation-Based Switching . . . . .	149
6.3.2	Reservation-Based Switching . . . . .	150
6.4	Mobility Models . . . . .	150
6.4.1	Direction-Persistent Mobility Model . . . . .	150
6.4.2	Direction-Non-persistent (DNP) Mobility Model . . . . .	155
6.5	Numerical Results . . . . .	157
6.5.1	Direction-Persistent Mobility Model . . . . .	157
6.5.2	Direction-Non-persistent Mobility Model . . . . .	161
6.6	Conclusions . . . . .	163
<b>7</b>	<b>Route Reservation in Ad Hoc Wireless Networks</b> . . . . .	<b>167</b>
7.1	Introduction . . . . .	167
7.2	Related Work . . . . .	168
7.3	Network Models and Assumptions . . . . .	169
7.3.1	Network Topology . . . . .	169
7.3.2	Typical Routes . . . . .	170
7.3.3	Bit Error Rate at the End of a Multi-hop Route . . . . .	170
7.3.4	Retransmission Model . . . . .	172
7.3.5	Mobility . . . . .	172
7.4	The Two Switching Schemes . . . . .	173
7.4.1	Reservation-Based Switching . . . . .	173
7.4.2	Non-reservation-Based Switching . . . . .	175
7.5	Analysis of the Two Switching Techniques . . . . .	176
7.5.1	Reservation-Based Switching . . . . .	176
7.5.2	Non-reservation-Based Switching . . . . .	179
7.6	Results and Discussion . . . . .	182
7.6.1	Switching Scheme and Traffic Load . . . . .	182
7.6.2	Effects of Interference . . . . .	183
7.6.3	Effects of the Number of Simultaneously Active Disjoint Routes . . . . .	188
7.6.4	Effects of Node Spatial Density . . . . .	189

7.6.5	Effects of Mobility . . . . .	191
7.6.6	Implications on Practical Scenarios . . . . .	192
7.7	Concluding Remarks . . . . .	193
<b>8</b>	<b>Optimal Common Transmit Power for Ad Hoc Wireless Networks</b>	<b>195</b>
8.1	Introduction . . . . .	195
8.2	Model and Assumptions . . . . .	196
8.2.1	Network Topology . . . . .	196
8.2.2	Routing . . . . .	197
8.2.3	Medium Access Control Protocol . . . . .	199
8.3	Connectivity . . . . .	199
8.3.1	Square Grid Topology . . . . .	200
8.3.2	Two-Dimensional Poisson Topology . . . . .	201
8.4	BER at the End of a Multi-hop Route . . . . .	202
8.4.1	Square Grid Topology . . . . .	202
8.4.2	Random Topology . . . . .	204
8.5	Optimal Common Transmit Power . . . . .	204
8.5.1	Optimal Common Transmit Power for Networks with Square Grid Topology . . . . .	204
8.5.2	Optimal Common Transmit Power for Networks with Random Topology . . . . .	205
8.6	Performance Metrics . . . . .	205
8.6.1	Node and Network Lifetime . . . . .	205
8.6.2	Effective Transport Capacity . . . . .	206
8.7	Results and Discussion . . . . .	208
8.7.1	Optimal Transmit Power and Data Rate . . . . .	208
8.7.2	Optimal Transmit Power and Node Spatial Density . . . . .	210
8.7.3	Effects of Strong Propagation Path Loss . . . . .	211
8.7.4	Connectivity Robustness to Node Spatial Density Changes . . . . .	213
8.7.5	Practical Determination of the Optimal Transmit Power . . . . .	215
8.8	Related Work . . . . .	216
8.9	Conclusions . . . . .	217
<b>9</b>	<b>The Routing Problem in Ad Hoc Wireless Networks: A Cross-Layer Perspective</b>	<b>219</b>
9.1	Introduction . . . . .	219
9.2	Experimental Evidence . . . . .	220
9.3	Preliminaries: Analytical Models and Assumptions . . . . .	221
9.3.1	Physical Layer . . . . .	221
9.3.2	Medium Access Control . . . . .	225
9.3.3	Basic Networking Assumptions . . . . .	226
9.4	Route Selection: Simulation Study . . . . .	227
9.4.1	Network Topology . . . . .	227
9.4.2	BER-Based Routing versus Shortest-Path Routing . . . . .	227
9.5	Network Performance Evaluation . . . . .	235
9.5.1	Average Hop Length Models . . . . .	235
9.5.2	Retransmission Model . . . . .	239

9.5.3	Packet Error Rate . . . . .	239
9.5.4	Delay . . . . .	240
9.6	Discussion . . . . .	243
9.6.1	Cross-layer Routing: A Practical Perspective . . . . .	243
9.6.2	Mobility . . . . .	246
9.7	Related Work . . . . .	246
9.8	Conclusions . . . . .	248
<b>10</b>	<b>Concluding Remarks</b>	<b>249</b>
10.1	Introduction . . . . .	249
10.2	Extensions of the Theoretical Framework: Open Problems . . . . .	249
10.2.1	Performance of Ad Hoc Wireless Networks: Random Versus Uniform Topologies . . . . .	249
10.2.2	Impact of Clustering on the BER Performance in Ad Hoc Wireless Networks . . . . .	251
10.2.3	Impact of Receiver Sensitivity on the Performance of Ad Hoc Wireless Networks . . . . .	253
10.2.4	Spectral Efficiency–Connectivity Tradeoff in Ad Hoc Wireless Networks . . . . .	254
10.2.5	MIMO-OFDM Wireless Communications . . . . .	256
10.2.6	Smart Antennas and Directional Antennas . . . . .	256
10.3	Network Architectures . . . . .	256
10.4	Network Application Architectures . . . . .	257
10.5	Standards . . . . .	258
10.6	Applications . . . . .	263
10.7	Conclusions . . . . .	264
<b>Appendix A</b>	<b>Analysis of the Inter-node Interference</b>	<b>265</b>
A.1	Introduction . . . . .	265
A.2	Exact Computation of the Average Link BER in a Scenario with Strong LOS	265
A.2.1	Interference from Nodes in Tier 1 . . . . .	266
A.2.2	Interference from Nodes in Tiers 1 and 2 . . . . .	271
A.2.3	Interference from Nodes in Tier 2 . . . . .	273
A.2.4	Simulation Scenario . . . . .	274
A.3	Exact Computation of the Average Link BER in a Scenario with Strong Multipath (Rayleigh Fading) . . . . .	276
A.3.1	Interference from Nodes in Tier 1 . . . . .	277
A.3.2	Interference from Nodes in Tiers 1 and 2 . . . . .	278
A.3.3	Interference from Nodes in Tiers 1, 2 and 3 . . . . .	278
A.4	LOS and Multipath (Rice Fading) . . . . .	280
A.5	Gaussian Assumption for the Interference Noise . . . . .	280
A.5.1	Route Bit Error Rate . . . . .	282
A.5.2	Interference Power . . . . .	284
<b>Appendix B</b>	<b>Proof of Theorem 1, Chapter 5</b>	<b>287</b>
<b>Appendix C</b>	<b>Route Discovery</b>	<b>293</b>

<b>Appendix D</b>	<b>Validation of Analytical Results</b>	<b>295</b>
D.1	Validation of Network Goodput . . . . .	295
D.2	Validation of Delay . . . . .	295
D.3	Validation of Average Number of Simultaneously Active Routes . . . . .	297
<b>Appendix E</b>	<b>Derivation of Joint CDF of <math>W</math> and <math>\Phi</math></b>	<b>299</b>
<b>References</b>		<b>307</b>
<b>Index</b>		<b>327</b>