

Contents

Acknowledgements.....	V
Introduction.....	1
1 Materials for Blown Film	5
1.1 Polymers	5
1.1.1 Polyethylene (PE)	6
1.1.2 Low-Density Polyethylene (LDPE)	6
1.1.3 High-Density Polyethylene (HDPE)	8
1.1.4 Linear Low-Density Polyethylene (LLDPE)	9
1.1.5 Metallocene Polyethylene (mPE).....	10
1.1.6 Polypropylene (PP).....	10
1.1.7 Polystyrene (PS).....	11
1.1.8 Ethylene Vinyl Acetate (EVA).....	12
1.1.9 Ethylene Vinyl Alcohol (EVOH).....	12
1.1.10 Polyvinyl Chloride (PVC).....	13
1.1.11 Polyamide (PA)	13
1.1.12 Polyurethane (PU).....	13
1.2 Additives	14
1.2.1 Antiblocking Agents	15
1.2.2 Antioxidants.....	15
1.2.3 Antistatic Agents	15
1.2.4 Colorants	16
1.2.5 Lubricants.....	17
1.2.6 Reinforcements and Fillers	17
1.2.7 Stabilizers	19
1.2.8 Tackifiers.....	19
2 Extrusion Overview.....	21
2.1 Extruder Hardware Systems	21
2.1.2 Drive System	23
2.1.2.1 Motor	23
2.1.2.2 Speed Reducer	23
2.1.2.3 Thrust Bearing.....	24
2.1.3 Feed System	26

2.1.4	Screw/Barrel System	28
2.1.4.1	Screw	28
2.1.4.2	Barrel	30
2.1.5	Head/Die System	31
2.1.5.1	Head Assembly	32
2.1.5.2	Adapter	32
2.1.5.3	Breaker Plate	32
2.1.5.4	Melt Filter	33
2.1.5.5	Die	35
2.1.6	Instrumentation and Control System	36
2.1.6.1	Temperature Control	37
2.1.6.2	Head Pressure	40
2.1.6.3	Motor Current	41
2.2	Extrusion Functional Zones	42
2.2.1	Solids Conveying	43
2.2.1.2	Gravity-Induced Region	43
2.2.1.3	Drag-Induced Region	44
2.2.2	Melting	45
2.2.3	Melt Pumping	47
2.2.4	Mixing	49
2.2.4.1	Distributive Mixing	49
2.2.4.2	Dispersive Mixing	50
2.2.4.3	Mixing Devices	51
2.2.5	Degassing	53
2.2.6	Die Forming	54
3	Hardware for Blown Film	59
3.1	Upstream Components	60
3.2	Grooved Feed Throat	62
3.3	Screws for Blown Film Extrusion	64
3.4	Blown Film Dies	65
3.5	Bubble Geometry	70
3.6	Bubble Cooling	73
3.7	Bubble Stabilization	78
3.8	Collapsing Frames	78
3.9	Haul-off	79
3.10	Winders	80
3.11	Film Treatment	82
3.12	Line Control	83

4	Processing	89
4.1	Process Variables vs. Bubble Geometry	90
4.2	Characteristic Bubble Ratios	92
4.3	Process/Structure/Property Relationships	94
5	Coextrusion	97
5.1	Dies	98
5.2	Interfacial Instabilities	100
6	Film Properties	103
6.1	Tensile Strength (ASTM D882)	105
6.2	Elongation (ASTM D882)	107
6.3	Tear Strength (ASTM D1004, ASTM D1922 and D1938)	107
6.4	Impact Resistance (ASTM D1709, D3420 and D4272)	109
6.5	Blocking Load (ASTM D3354) and Coefficient of Friction (ASTM D1894)	110
6.6	Gel (Fisheye) Count (ASTM D3351 and D3596)	111
6.7	Low Temperature Brittleness (ASTM D1790)	111
6.8	Gloss (ASTM D2457)	112
6.9	Transparency (ASTM D1746)	112
6.10	Haze (ASTM D1003)	113
6.11	Density (ASTM D1505)	113
6.12	Melt Index (ASTM D1238)	114
6.13	Viscosity by Capillary Rheometry (ASTM D3835)	116
7	Troubleshooting	119
7.1	Extruder Problems	120
7.1.1	Surging	120
7.1.2	High Melt Temperature	121
7.1.3	Excessive Cooling	123
7.1.4	Low Output	124
7.2	Film Problems	125
7.2.1	Melt Fracture	125
7.2.2	Thickness Variation	126
7.2.3	Die Lines	130
7.2.4	Gels	131
7.2.5	Low Mechanical Properties	132
7.2.6	Poor Optical Properties	133

Appendix A: The Blown Film Extrusion Simulator135

 A.1 Introduction135

 A.2 Installation136

 A.3 Running the Program137

 A.4 Worksheet144

Appendix B: Useful Equations147

References155

Subject Index159