

Contents

1	Introduction	1
1.1	Organization of the Book	3
2	Modelling Issue in Fault Diagnosis	7
2.1	Problem of Fault Detection and Fault Diagnosis	8
2.2	Models Used in Fault Diagnosis	11
2.2.1	Parameter Estimation	12
2.2.2	Parity Relations	12
2.2.3	Observers	13
2.2.4	Neural Networks	14
2.2.5	Fuzzy Logic	15
2.3	Neural Networks in Fault Diagnosis	16
2.3.1	Multi-layer Feedforward Networks	16
2.3.2	Radial Basis Function Network	18
2.3.3	Kohonen Network	20
2.3.4	Model Based Approaches	21
2.3.5	Knowledge Based Approaches	23
2.3.6	Data Analysis Approaches	23
2.4	Evaluation of the FDI System	24
2.5	Summary	26
3	Locally Recurrent Neural Networks	29
3.1	Neural Networks with External Dynamics	30
3.2	Fully Recurrent Networks	31
3.3	Partially Recurrent Networks	32
3.4	State-Space Networks	34
3.5	Locally Recurrent Networks	36
3.5.1	Model with the IIR Filter	40
3.5.2	Analysis of Equilibrium Points	43
3.5.3	Controllability and Observability	47
3.5.4	Dynamic Neural Network	49
3.6	Training of the Network	52

3.6.1	Extended Dynamic Back-Propagation	52
3.6.2	Adaptive Random Search	53
3.6.3	Simultaneous Perturbation Stochastic Approximation ...	55
3.6.4	Comparison of Training Algorithms	57
3.7	Summary	62
4	Approximation Abilities of Locally Recurrent Networks	65
4.1	Modelling Properties of the Dynamic Neuron	66
4.1.1	State-Space Representation of the Network	67
4.2	Preliminaries	67
4.3	Approximation Abilities	68
4.4	Process Modelling	72
4.5	Summary	74
5	Stability and Stabilization of Locally Recurrent Networks ..	77
5.1	Stability Analysis – Networks with One Hidden Layer	78
5.1.1	Gradient Projection	82
5.1.2	Minimum Distance Projection	82
5.1.3	Strong Convergence	86
5.1.4	Numerical Complexity	88
5.1.5	Pole Placement	90
5.1.6	System Identification Based on Real Process Data	92
5.1.7	Convergence of Network States	93
5.2	Stability Analysis – Networks with Two Hidden Layers	96
5.2.1	Second Method of Lyapunov	97
5.2.2	First Method of Lyapunov	105
5.3	Stability Analysis – Cascade Networks	110
5.4	Summary	111
6	Optimum Experimental Design for Locally Recurrent Networks	113
6.1	Optimal Sequence Selection Problem in Question	114
6.1.1	Statistical Model	114
6.1.2	Sequence Quality Measure	115
6.1.3	Experimental Design	116
6.2	Characterization of Optimal Solutions	117
6.3	Selection of Training Sequences	118
6.4	Illustrative Example	119
6.4.1	Simulation Setting	119
6.4.2	Results	120
6.5	Summary	121
7	Decision Making in Fault Detection	123
7.1	Simple Thresholding	124
7.2	Density Estimation	126
7.2.1	Normality Testing	126

7.2.2	Density Estimation	127
7.2.3	Threshold Calculating – A Single Neuron.....	130
7.2.4	Threshold Calculating – A Two-Layer Network.....	131
7.3	Robust Fault Diagnosis	132
7.3.1	Adaptive Thresholds.....	133
7.3.2	Fuzzy Threshold Adaptation.....	135
7.3.3	Model Error Modelling.....	137
7.4	Summary.....	140
8	Industrial Applications	141
8.1	Sugar Factory Fault Diagnosis	141
8.1.1	Instrumentation Faults.....	143
8.1.2	Actuator Faults	143
8.1.3	Experiments	146
8.1.4	Final Remarks	160
8.2	Fluid Catalytic Cracking Fault Detection	161
8.2.1	Process Modelling	163
8.2.2	Faulty Scenarios.....	164
8.2.3	Fault Diagnosis	164
8.2.4	Robust Fault Diagnosis	168
8.2.5	Final Remarks	172
8.3	DC Motor Fault Diagnosis	172
8.3.1	AMIRA DR300 Laboratory System	173
8.3.2	Motor Modelling	176
8.3.3	Fault Diagnosis Using Density Shaping.....	176
8.3.4	Robust Fault Diagnosis	181
8.3.5	Final Remarks	182
9	Concluding Remarks and Further Research Directions	187
	References.....	191
	Index.....	203

List of Figures

2.1	Scheme of the diagnosed automatic control system	8
2.2	Types of faults: abrupt (dashed), incipient (solid) and intermittent (dash-dot)	9
2.3	Two stages of fault diagnosis	10
2.4	General scheme of model based fault diagnosis	11
2.5	Neuron scheme with n inputs and one output	17
2.6	Three layer perceptron with n inputs and m outputs	18
2.7	Structure of the radial basis function network with n inputs and m outputs	19
2.8	Model based fault diagnosis using neural networks	22
2.9	Model-free fault diagnosis using neural networks	24
2.10	Fault diagnosis as pattern recognition	25
2.11	Definition of the benchmark zone	25
3.1	External dynamics approach realization	30
3.2	Fully recurrent network of Williams and Zipser	32
3.3	Partially recurrent networks due to Elman (a) and Jordan (b) . . .	33
3.4	Architecture of the recurrent multi-layer perceptron	34
3.5	Block scheme of the state-space neural network with one hidden layer	34
3.6	Generalized structure of the dynamic neuron unit (a), network composed of dynamic neural units (b)	36
3.7	Neuron architecture with local activation feedback	39
3.8	Neuron architecture with local synapse feedback	39
3.9	Neuron architecture with local output feedback	40
3.10	Memory neuron architecture	41
3.11	Neuron architecture with the IIR filter	41
3.12	Transformation of the neuron model with the IIR filter to the general local activation feedback structure	42
3.13	State-space form of the i -th neuron with the IIR filter	43

3.14	Positions of equilibrium points: stable node (a), stable focus (b), unstable node (c), unstable focus (d), saddle point (e), center (f)	44
3.15	Eigenvalue positions of the matrix \mathbf{A} : $\gamma = 0.3$ (a), $\gamma = 0.5$ (b) . . .	45
3.16	Eigenvalue positions of the modified matrix \mathbf{A} : $\gamma = 0.3$ (a), $\gamma = 0.5$ (b)	46
3.17	Topology of the locally recurrent globally feedforward network	50
3.18	Learning error for different algorithms	60
3.19	Testing phase: EDBP (a), ARS (b) and SPSA (c). Actuator (black), neural model (grey)	61
4.1	i -th neuron of the second layer	70
4.2	Cascade structure of the modified dynamic neural network	70
4.3	Cascade structure of the modified dynamic neural network	72
5.1	Result of the experiment – an unstable system	80
5.2	Result of the experiment – a stable system	81
5.3	Idea of the gradient projection	83
5.4	Stability triangle and the search region	84
5.5	Sum squared error – training without stabilization	90
5.6	Poles location during learning without stabilization: neuron 1 (a), neuron 2 (b), neuron 3 (c), neuron 4 (d)	91
5.7	Poles location during learning, stabilization using GP: neuron 1 (a), neuron 2 (b), neuron 3 (c), neuron 4 (d)	92
5.8	Poles location during learning without stabilization: neuron 1 (a), neuron 2 (b), neuron 3 (c), neuron 4 (d)	93
5.9	Poles location during learning, stabilization using MDP: neuron 1 (a), neuron 2 (b), neuron 3 (c), neuron 4 (d)	94
5.10	Actuator (solid line) and model (dashed line) outputs for learning (a) and testing (b) data sets	94
5.11	Results of training without stabilization: error curve (a) and the convergence of the state $\mathbf{x}(k)$ of the neural model (b)	95
5.12	Results of training with GP: error curve (a) and the convergence of the state $\mathbf{x}(k)$ of the neural model (b)	95
5.13	Results of training with MDP: error curve (a) and the convergence of the state $\mathbf{x}(k)$ of the neural model (b)	96
5.14	Convergence of network states: original system (a)–(b), transformed system (c)–(d), learning track (e)	99
5.15	Convergence of network states: original system (a)–(b), transformed system (c)–(d), learning track (e)	102
5.16	Graphical solution of the problems (5.70)	109
6.1	Convergence of the design algorithm	120
6.2	Average variance of the model response prediction for optimum design (diamonds) and random design (circles)	121

7.1	Residual with thresholds calculated using: (7.3) (a), (7.5) with $\zeta = 1$ (b), (7.5) with $\zeta = 2$ (c), (7.5) with $\zeta = 3$ (d)	125
7.2	Normality testing: comparison of cumulative distribution functions (a), probability plot (b)	127
7.3	Neural network for density calculation	129
7.4	Simple two-layer network	129
7.5	Output of the network (7.20) with the threshold (7.34)	131
7.6	Residual signal (solid), adaptive thresholds calculated using (7.38) (dotted), and adaptive thresholds calculated using (7.39) (dashed)	135
7.7	Illustration of the fuzzy threshold adaptation	136
7.8	Scheme of the fault detection system with the threshold adaptation	137
7.9	Idea of the fuzzy threshold	137
7.10	Model error modelling: error model training (a), confidence region constructing (b)	138
7.11	Idea of model error modelling: system output (solid), centre of the uncertainty region (dotted), confidence bands (dashed)	139
8.1	Evaporation station. Four heaters and the first evaporation section	142
8.2	Actuator to be diagnosed (a), block scheme of the actuator (b)	144
8.3	Causal graph of the main actuator variables	145
8.4	Residual signal for the vapour model in different faulty situations: fault in $P51.03$ (900–1200), fault in $T51.07$ (1800–2100)	148
8.5	Residual signals for the temperature model in different faulty situations: fault in $F51.01$ (0–300), fault in $F51.02$ (325–605), fault in $T51.06$ (1500–1800), fault in $T51.08$ (2100–2400), fault in $TC51.05$ (2450–2750)	149
8.6	Normal operating conditions: residual with the constant (a) and the adaptive (b) threshold	151
8.7	Residual for different faulty situations	152
8.8	Residual of the nominal model (output F) in the case of the faults f_1 (a), f_2 (b) and f_3 (c)	154
8.9	Residual of the nominal model (output X) in the case of the faults f_1 (a), f_2 (b) and f_3 (c)	155
8.10	Residuals of the fault models f_1 (a) and (d); f_2 (b) and (e); f_3 (c) and (f) in the case of the fault f_1	156
8.11	Residuals of the fault models f_1 (a) and (d); f_2 (b) and (e); f_3 (c) and (f) in the case of the fault f_2	157
8.12	Residuals of the fault models f_1 (a) and (d); f_2 (b) and (e); f_3 (c) and (f) in the case of the fault f_3	158
8.13	General scheme of the fluid catalytic cracking converter	162

8.14	Results of modelling the temperature of the cracking mixture (8.9)	163
8.15	Residual signal	164
8.16	Cumulative distribution functions: normal – solid, residual – dashed	165
8.17	Probability plot for the residual	165
8.18	Residual histogram (a), network output histogram (b), estimated PDF and the confidence interval (c)	166
8.19	Residual histogram (a), network output histogram (b), estimated PDF and the confidence interval (c)	167
8.20	Residual (solid) and the error model output (dashed) under nominal operating conditions	169
8.21	Confidence bands and the system output under nominal operating conditions	170
8.22	Residual with constant thresholds under nominal operating conditions	170
8.23	Fault detection results: scenario f_1 (a), scenario f_2 (b), scenario f_3 (c)	171
8.24	Laboratory system with a DC motor	174
8.25	Equivalent electrical circuit of a DC motor	176
8.26	Responses of the motor (solid) and the neural model (dash-dot) – open-loop control	177
8.27	Responses of the motor (solid) and the neural model (dashed) – closed-loop control	177
8.28	Symptom distribution	179
8.29	Residual and constant thresholds (a) and confidence bands generated by model error modelling (b)	182
8.30	Fault detection using model error modelling: fault f_1^1 – confidence bands (a) and decision logic without the time window (b); fault f_6^1 – confidence bands (c) and decision logic without the time window (d); fault f_4^2 – confidence bands (e) and decision logic without the time window (f)	183
8.31	Fault detection by using constant thresholds: fault f_1^1 – residual with thresholds (a) and decision logic without the time window (b); fault f_6^1 – residual with thresholds (c) and decision logic without the time window (d); fault f_4^2 – residual with thresholds (e) and decision logic without the time window (f)	184

List of Tables

3.1	Specification of different types of dynamic neuron units	38
3.2	Outline of ARS	55
3.3	Outline of the basic SPSA	57
3.4	Characteristics of learning methods	59
3.5	Characteristics of learning methods	62
4.1	Selection results of the cascade dynamic neural network	73
4.2	Selection results of the two-layer dynamic neural network	73
5.1	Outline of the gradient projection	83
5.2	Outline of the minimum distance projection	86
5.3	Number of operations: GP method	89
5.4	Number of operations: MDP method	89
5.5	Comparison of the learning time for different methods	90
5.6	Outline of norm stability checking	100
5.7	Comparison of methods	105
5.8	Outline of constrained optimisation training	110
6.1	Sample mean and the standard deviation of parameter estimates	120
7.1	Threshold calculating	132
8.1	Specification of process variables	143
8.2	Description of symbols	144
8.3	Selection of the neural network for the vapour model	148
8.4	Number of false alarms	150
8.5	Neural models for nominal conditions and faulty scenarios	153
8.6	Results of fault detection (a) and isolation (b) (X – detectable/isolable, N – not detectable/not isolable)	159
8.7	Modelling quality for different models	159

8.8	FDI properties of the examined approaches	160
8.9	Specification of measurable process variables	163
8.10	Comparison of false detection rates	168
8.11	Performance indices for faulty scenarios	168
8.12	Performance indices for faulty scenarios	169
8.13	Laboratory system technical data	175
8.14	Results of fault detection for the density shaping technique	178
8.15	Fault isolation results	180
8.16	Fault identification results	181
8.17	Results of fault detection for model error modelling	185