

# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Quantum computing . . . . .	1
1.1.1	Methods . . . . .	3
1.2	Ion trap quantum computers . . . . .	3
1.3	Thesis outline . . . . .	6
<b>2</b>	<b>Theory</b>	<b>9</b>
2.1	Ion traps . . . . .	9
2.1.1	Mathieu Equation . . . . .	10
2.1.2	Recent ion trap developments . . . . .	13
2.2	Ytterbium . . . . .	14
2.2.1	Photoionization . . . . .	14
2.2.2	Ionic schemes . . . . .	15
2.2.3	Preparation method calculations . . . . .	18
2.2.4	935 nm system calculations . . . . .	21
2.3	Laser cooling . . . . .	24
2.3.1	Doppler cooling . . . . .	24
2.3.2	Sideband cooling . . . . .	27
2.4	Qubit dynamics . . . . .	29
2.5	Gradient scheme . . . . .	32
2.5.1	Pros and cons of the Gradient scheme . . . . .	36
2.6	Pulses . . . . .	37
2.6.1	Optimal control theory (OCT) pulses . . . . .	38

2.6.2	Composite pulses . . . . .	40
2.6.3	Pulse simulations . . . . .	41
2.7	Decoherence . . . . .	43
2.7.1	Decoherence Free subspace (DFS) . . . . .	44
2.8	Alternative gradient scheme . . . . .	45
2.8.1	Dressed state picture . . . . .	46
2.8.2	From noisy to stable transitions . . . . .	52
2.8.3	Two level system dressed state based scheme . . . . .	54
2.8.4	Possible dressed state based $^{171}\text{Yb}^+$ qubits . . . . .	56
<b>3</b>	<b>Experimental Description</b>	<b>61</b>
3.1	Trap description . . . . .	61
3.2	Optical set up . . . . .	64
3.2.1	Solid state system: 369 nm . . . . .	64
3.2.2	Diode laser system: 935 nm, 638 nm, 399 nm . . . . .	67
3.2.3	$\lambda$ -meter . . . . .	68
3.3	Non optical fields. . . . .	69
3.3.1	Microwave . . . . .	69
3.3.2	Radio frequency fields. . . . .	72
3.3.3	Static fields. . . . .	74
3.4	Detection . . . . .	75
3.5	Experimental control . . . . .	76
3.6	Data evaluation . . . . .	80
3.6.1	Poissonian statistics . . . . .	80
3.6.2	Time resolved detection . . . . .	83
<b>4</b>	<b>Pulse Measurements</b>	<b>87</b>
4.1	Measuring pulse fidelities . . . . .	87
4.1.1	Measuring pulse fidelities: what was measured . . . . .	87
4.1.2	Measuring pulse fidelities: how to measure it . . . . .	89

4.2	Optimal Control Theory based pulses . . . . .	91
4.3	Composite pulses . . . . .	94
4.4	Summary . . . . .	97
<b>5</b>	<b>Bare State Measurements</b>	<b>99</b>
5.1	Preparation improvement. . . . .	99
5.2	935 dependence . . . . .	102
5.3	Detection efficiency . . . . .	104
5.4	Measurements of magnetic field sensitive levels . . . . .	105
5.5	Coherences after a 50 Hz trigger . . . . .	107
5.6	Summary . . . . .	111
<b>6</b>	<b>Dressed States</b>	<b>113</b>
6.1	Preparation methods . . . . .	113
6.1.1	Robustness of STIRAP . . . . .	117
6.1.2	Adiabatic preparation of a 2-level dressed state system. . . . .	124
6.2	Two level operations on dressed states . . . . .	127
6.3	Three level system . . . . .	130
6.4	Summary . . . . .	136
<b>7</b>	<b>Conclusion</b>	<b>137</b>
<b>A</b>	<b>Dipole moment calculation</b>	<b>141</b>
A.1	Coupling constants . . . . .	141
A.1.1	Electric dipole moments . . . . .	143
A.1.2	$jk$ coupling . . . . .	145
A.2	$^{171}\text{Yb}^+$ . . . . .	146
<b>B</b>	<b>Optical Bloch Equations</b>	<b>155</b>
B.1	Many level systems . . . . .	157
B.1.1	2 level system . . . . .	157

B.1.2 3 level system . . . . .	158
B.1.3 8 level system (369 nm) . . . . .	160
B.1.4 20 level system (369 nm + 935 nm) . . . . .	162
<b>C Magnetic Field Dependence</b>	<b>165</b>
<b>D Pulse support</b>	<b>167</b>
D.1 Ramsey phase probe result . . . . .	167
D.2 Quaternion simulations . . . . .	169
<b>E Circuits</b>	<b>173</b>
E.1 Phase lock loop . . . . .	173
E.2 50 Hz TTL signal . . . . .	174
<b>F Program Catalogue</b>	<b>177</b>
F.1 Mfile packages . . . . .	177
F.1.1 Rabi measurements . . . . .	178
F.1.2 Ramsey measurements . . . . .	180
F.1.3 Pulses . . . . .	181
F.1.4 Simulations . . . . .	182
F.2 Mathematica files . . . . .	184
F.3 Vi libraries . . . . .	185
<b>G Devices</b>	<b>191</b>
G.1 $^{171}\text{Yb}^+$ trap experiment equipment list . . . . .	191
<b>Bibliography</b>	<b>195</b>
<b>Acknowledgements</b>	<b>203</b>