

PREFACE	II
ABSTRACT	III
CONTENTS	IV
Chapters	
1. Introduction	1
2. The model	2
• Activities and building methods	2
• The building process	3
3. The size of the project	5
• Pyramid and casing	5
• Linear ramp	5
• Spiral ramp	7
• Other ramps	7
4. The efficiency of manual labour	7
• Definitions of unit performance	7
• Quarrying	8
• Excavation of a canal	13
• Brick production	14
• Transportation	15
5. How many man-hours?	26
6. Workforce and work schedule	29
• Total workforce	29
• Time	30
• Building rate	31
• Workforce for the various activities	33
7. Combination of a ramp with levering	36
• Conditions and summary of results	36
• Transition between successive phases	38
• The levering phase	39
• Hindsight versus foresight	43
8. Area per builder and hauling trains	44
• Minimum area per builder	44
• Available areas	44
• Number of hauling trains	46

9. Numerical example	47
10. Discussion of basic data	49
11. Placing the pyramidion (by K. J. Weber)	50
12. The building materials (by K. J. Weber)	53
• The Giza limestone	53
• The Tura limestone	59
• Granite	59
13. Literature review	59
14. Conclusions	78

Appendices

1. Volumes of pyramid and casing	80
2. Volume of linear ramp	81
3. Volume of spiral ramp	84
4. Manpower	87
5. Workforce, time and rate	92
6. Combination of a ramp with levering	98
7. Area per builder	102
8. Transportation	104
9. How does it work for a mini-pyramid?	110

Bibliography	112
---------------------	-----

Illustration sources	114
-----------------------------	-----

Tables attached

I. Unit performance for transportation – literature data	115
II. Basic data	116
III. Some results	117

Figures attached

A.2.1 Exterior ramp - cross-section	118
A.2.2 Exterior ramp - base areas	118
A.2.3 Interior ramp - cross-section	118
A.2.4 Staircase - cross-section	118
A.3.1 Spiral ramp schematically	119
A.3.2 Spiral ramp - cross-section	119

A.3.3 Spiral ramp – calculation	119
A.7.1 Available area for levering on side of the pyramid	120
A.8.1 Force diagram	120
A.8.2 Number of blocks arriving per unit time	120
A.8.3 Stepwise displacement by levering	120
Author Index	121
Subject Index	122
List of symbols and units used	124
Tables in text	
4.1 Hauling experiment	19
6.1 Total workforce for the various building methods	29
7.1 Results for the combination method	37
7.2 Exterior ramp, base case - Workforce by activity vs height	41
7.3 Interior ramp, base case - Workforce by activity vs height	41
8.1 Numerical values for the for the levering method - Volume equations	47
8.2 Numerical values for the for the levering method - Manpower equations	48
12.1 Layer thickness of Sphinx and Pyramid	55
13.1 Literature review	61
13.2 Workforce corresponding with pyramid building in series	66
13.3 Comparison with Romer’s workforce numbers	69
13.4 Matching Romer’s volume curve	69
13.5 Characteristics of some model curves	71
13.6 Stone production	72
Tables in Appendices	
4-1 Volume equations for pyramid, casing and ramps	88
4-2 Manpower equations for the various activities	91
9-1 Calculations for mini-pyramid	110

Figures in text

1.1 Map of ancient Egypt	X
1.2 The Cheops pyramid	1
2.1 Project schedule of the pyramid construction	2
2.2 Exterior and interior linear ramp	3
2.3 Spiral ramp	3
2.4 Material flow	4
3.1 Calculation of volume linear ramp	6
3.2 Cross-section of linear ramp for successive stages	6
3.3 Ratio of ramp/pyramid volumes vs relative height	6
3.4 Ratio of interior/exterior ramp volumes vs relative total height	6
4.1 Giza plateau with possible orientation of linear ramp	9
4.2 Quarrying limestone	10
4.3 North face of Meidum pyramid showing undressed inner stones	11
4.4 Unfinished obelisk at Aswan	12
4.5 Granite quarrying squatting	12
4.6 Granite quarrying standing	12
4.7 Transport of Djehutihotep monument	16
4.8 Hauling a block up the ramp	17
4.9 Levering	24
5.1 Calculation of the average horizontal distance	27
5.2 Total manpower versus fraction of pyramid completed	28
5.3 Fractional manpower for the various activities	28
6.1 Calculation scheme	30
6.2 Fraction of pyramid completed versus time	30
6.3 Block travel time	30
6.4 Effective building rate versus fraction of pyramid completed	31
6.5 Adjusted building rate versus fraction of pyramid completed	31
6.6 Simultaneous ramp and pyramid building	32
6.7 Number of builders as a fraction of total workforce, vs fraction of pyramid completed	33
6.8 Workforce vs time for exterior ramp of 133 m	34
6.9 Workforce vs time for spiral ramp of 133 m	34
6.10 Workforce vs time for levering	34
6.11 Shipping workforce versus fraction of pyramid completed	33
7.1 Workforce vs time for exterior ramp of 82 m	40
7.2 Workforce vs time for interior ramp of 82 m	40
7.3 Workforce vs time for spiral ramp of 82 m	40

7.4 Height of pyramid in cubits versus thickness layers in metres	42
8.1 Area per hauling team	44
8.2 Horizontal area per builder versus fraction of pyramid completed	45
8.3 Inclined area per builder versus fraction of pyramid completed	45
8.4 Minimum number of hauling trains vs time for linear ramp	46
8.5 Minimum number of hauling trains vs time for spiral ramp	46
11.1 Seagoing vessel dating from about 2500 B.C.	51
11.2 H-shaped hoist	51
11.3 Bearing stones of the fourth dynasty	52
11.4 Placing the topmost layers	52
12.1 Section of a nummulites limestone	53
12.2 Detail of a nummulites limestone	54
12.3 Chephren quarry showing the trenches around the removed building blocks	54
12.4 Side view of the Sphinx showing the constant thickness of the layers	55
12.5 The Sphinx prior to the extensive restoration	56
12.6 Cross-section of the Mokattam formation	60
12.7 Estimated contour map of the quarry area prior to the excavation	57
12.8 Estimated contour map of the quarry area on completion of the excavation	57
12.9 Thin section of Tura limestone	60
13.1 Stone production for the construction of pyramids	65
13.2 Matching Romer' building schedule	70
13.3 Romer's building schedule vs model curves	71
13.4 Effect of early start of quarrying on volume to be stored	76
A.9.1 Mini-pyramid	110
A.9.2 Workforce for mini-pyramid vs time in hours	111