



INTERNATIONAL TELECOMMUNICATION UNION

# CCITT

THE INTERNATIONAL  
TELEGRAPH AND TELEPHONE  
CONSULTATIVE COMMITTEE

BLUE BOOK

---

VOLUME III – FASCICLE III.2

## INTERNATIONAL ANALOGUE CARRIER SYSTEMS

RECOMMENDATIONS G.211-G.544

UNIVERSITÄTSBIBLIOTHEK  
HANNOVER  
TECHNISCHE  
INFORMATIONSBIBLIOTHEK



IXTH PLENARY ASSEMBLY  
MELBOURNE, 14-25 NOVEMBER 1988

Geneva 1989

ISBN 92-61-03321-0

UB/TIB Hannover 89

115 565 981



## CONTENTS OF FASCICLE III.2 OF THE BLUE BOOK

### Part I – Recommendations G.211 to G.544

#### Line transmission

#### International analogue carrier systems

Rec. No.		Page
SECTION 2 – <i>General characteristics common to all analogue carrier-transmission systems</i>		
2.1 Definitions and general considerations		
G.211	Make-up of a carrier link . . . . .	3
G.212	Hypothetical reference circuits for analogue systems . . . . .	10
G.213	Interconnection of systems in a main repeater station . . . . .	12
G.214	Line stability of cable systems . . . . .	16
G.215	Hypothetical reference circuit of 5000 km for analogue systems . . . . .	17
2.2 General recommendations		
G.221	Overall recommendations relating to carrier-transmission systems . . . . .	18
G.222	Noise objectives for design of carrier-transmission systems of 2500 km . . . . .	20
G.223	Assumptions for the calculation of noise on hypothetical reference circuits for telephony . . . . .	23
G.224	Maximum permissible value for the absolute power level (power referred to one milliwatt) of a signalling pulse . . . . .	32
G.225	Recommendations relating to the accuracy of carrier frequencies . . . . .	32
G.226	Noise on a real link . . . . .	34
G.227	Conventional telephone signal . . . . .	35
G.228	Measurement of circuit noise in cable systems using a uniform-spectrum random noise loading . . . . .	38
G.229	Unwanted modulation and phase jitter . . . . .	49

Rec. No.		Page
<b>2.3</b>	<b>Translating equipment used on various carrier-transmission systems</b>	
G.230	Measuring methods for noise produced by modulating equipment and through-connection filters . . . . .	50
G.231	Arrangement of carrier equipment . . . . .	54
G.232	12-channel terminal equipments . . . . .	55
G.233	Recommendations concerning translating equipments . . . . .	67
G.234	8-channel terminal equipments . . . . .	76
G.235	16-channel terminal equipments . . . . .	76
<b>2.4</b>	<b>Utilization of groups, supergroups, etc.</b>	
G.241	Pilots on groups, supergroups, etc. . . . .	79
G.242	Through-connection of groups, supergroups, etc. . . . .	84
G.243	Protection of pilots and additional measuring frequencies at points where there is a through-connection . . . . .	91
 <b>SECTION 3 – <i>Individual characteristics of international carrier telephone systems on metallic lines</i></b>		
<b>3.1</b>	<b>Systems providing a group on an open-wire pair</b>	
G.311	General characteristics of systems providing 12 carrier telephone circuits on an open-wire pair . . . . .	97
G.312	Intermediate repeaters for open-wire carrier systems conforming to Recommendation G.311 . . . . .	102
G.313	Open-wire lines for use with 12-channel carrier systems . . . . .	103
G.314	General characteristics of systems providing eight carrier telephone circuits on an open-wire pair . . . . .	105
<b>3.2</b>	<b>Carrier telephone systems on unloaded symmetric cable pairs, providing groups or supergroups</b>	
G.322	General characteristics recommended for systems on symmetric pair cables . . . . .	106
G.323	A typical transistorized system on symmetric cable pairs . . . . .	113
G.324	General characteristics for valve-type systems on symmetric cable pairs . . . . .	115
G.325	General characteristics recommended for systems providing 12 telephone carrier circuits on a symmetric cable pair [(12 + 12) systems] . . . . .	115
G.326	Typical systems on symmetric cable pairs [(12 + 12) systems] . . . . .	119
G.327	Valve-type systems offering 12 carrier telephone circuits on a symmetric cable pair [(12 + 12) systems] . . . . .	121
<b>VIII</b>	<b>Fascicle III.2 – Table of Contents</b>	

Rec. No.		Page
<b>3.3</b>	<b>Carrier systems on 2.6/9.5 mm coaxial cable pairs</b>	
G.332	12 MHz systems on standardized 2.6/9.5 mm coaxial cable pairs . . . . .	122
G.333	60 MHz systems on standardized 2.6/9.5 mm coaxial cable pairs . . . . .	132
G.334	18 MHz systems on standardized 2.6/9.5 mm coaxial cable pairs . . . . .	141
G.337	General characteristics of systems on 2.6/9.5 mm coaxial cable pairs . . . . .	149
G.338	4 MHz valve-type systems on standardized 2.6/9.5 mm coaxial cable pairs . . . . .	149
<b>3.4</b>	<b>Carrier systems on 1.2/4.4 mm coaxial cable pairs</b>	
G.339	12 MHz valve-type systems on standardized 2.6/9.5 mm coaxial cable pairs . . . . .	150
G.341	1.3 MHz systems on standardized 1.2/4.4 mm coaxial cable pairs . . . . .	151
G.343	4 MHz systems on standardized 1.2/4.4 mm coaxial cable pairs . . . . .	155
G.344	6 MHz systems on standardized 1.2/4.4 mm coaxial cable pairs . . . . .	158
G.345	12 MHz systems on standardized 1.2/4.4 mm coaxial cable pairs . . . . .	161
G.346	18 MHz systems on standardized 1.2/4.4 mm coaxial cable pairs . . . . .	161
<b>3.5</b>	<b>Additional Recommendations on cable systems</b>	
G.352	Interconnection of coaxial carrier systems of different designs . . . . .	161
G.356	(120 + 120) channel systems on a single coaxial pair . . . . .	164
<b>3.6</b>	<b>Other carrier systems on open-wire lines</b>	
G.361	Systems providing three carrier telephone circuits on a pair of open-wire lines . . . . .	165
<b>3.7</b>	<b>International telephone carrier systems using submarine cable</b>	
G.371	FDM carrier systems for submarine cable . . . . .	169
 <b>SECTION 4 – <i>General characteristics of international carrier telephone systems on radio-relay or satellite links and interconnection with metallic lines. Coordination of radiotelephony and line telephony</i></b>		
<b>4.1</b>	<b>General recommendations</b>	
G.411	Use of radio-relay systems for international telephone circuits . . . . .	173
G.412	Terminal equipments of radio-relay systems forming part of a general telecommunication network . . . . .	174
<b>4.2</b>	<b>Interconnection of radio-relay links with carrier systems on metallic lines</b>	
G.421	Methods of interconnection . . . . .	174
G.422	Interconnection at audio-frequencies . . . . .	175
G.423	Interconnection at the baseband frequencies of frequency-division multiplex radio-relay systems . . . . .	176

Rec. No.		Page
<b>4.3</b>	<b>Hypothetical reference circuits</b>	
G.431	Hypothetical reference circuits for frequency-division multiplex radio-relay systems . . .	183
G.433	Hypothetical reference circuit for trans-horizon radio-relay systems for telephony using frequency-division multiplex . . . . .	184
G.434	Hypothetical reference circuit for systems using analogue transmission in the fixed-satellite service . . . . .	184
<b>4.4</b>	<b>Circuit noise</b>	
G.441	Permissible circuit noise on frequency-division multiplex radio-relay systems . . . . .	185
G.442	Radio-relay system design objectives for noise at the far end of a hypothetical reference circuit with reference to telegraphy transmission . . . . .	186
G.444	Allowable noise power in the hypothetical reference circuit of trans-horizon radio-relay systems for telephony using frequency-division multiplex . . . . .	187
G.445	Allowable noise power in the hypothetical reference circuit for frequency-division multiplex telephony in the fixed-satellite service . . . . .	187
<b>4.5</b>	<b>Radiotelephone circuits</b>	
G.451	Use of radio links in international telephone circuits . . . . .	187
G.453	Improved transmission system for HF radio-telephone circuits . . . . .	189
<b>4.6</b>	<b>Devices associated with radiotelephone circuits</b>	
G.464	Principles of the devices used to achieve privacy in radiotelephone conversations . . . .	189
<b>4.7</b>	<b>Links with mobile stations</b>	
G.471	Conditions necessary for interconnection of mobile radiotelephone stations and international telephone lines . . . . .	190
G.473	Interconnection of a maritime mobile satellite system with the international automatic switched telephone service; transmission aspects . . . . .	190
 <b>SECTION 5 – <i>Audio-frequency circuits</i></b>		
<b>5.4</b>	<b>Specifications recommended by the CCITT for audio-frequency cable circuits</b>	
G.541	Specification of factory lengths of loaded telecommunication cable . . . . .	202
G.542	Specification of loading coils for loaded telecommunication cables . . . . .	202
G.543	Specification for repeater sections of loaded telecommunication cable . . . . .	202
G.544	Specifications for terminal equipment and intermediate repeater stations . . . . .	202

Part II – Sections 2 to 5 of the Series G Recommendations

Rec. No.		Page
Supplement No. 4	Certain methods of avoiding the transmission of excessive noise between interconnected systems . . . . .	205
Supplement No. 5	Measurement of the load of telephone circuits under field conditions . . . . .	205
Supplement No. 6	Example showing how the total value of line noise specified for the hypothetical reference circuit on open-wire lines might be broken down into its various components . . . . .	205
Supplement No. 7	Loss-frequency response of channel-translating equipment used in some countries for international circuits . . . . .	205
Supplement No. 8	Method proposed by the Belgian telephone administration for interconnection between coaxial and symmetric pair systems . . . . .	205
Supplement No. 9	Roll effect in coaxial pair systems . . . . .	206
Supplement No. 13	Noise at the terminals of the battery supply . . . . .	206
Supplement No. 17	Group-delay distortion performance of terminal equipment . . . . .	206
Supplement No. 22	Mathematical models of multiplex signals . . . . .	206
Supplement No. 23	Explanatory notes for the information of designers of a maritime mobile satellite system . . . . .	206
Supplement No. 26	Estimating the signal load margin of FDM wideband amplifier equipment and transmission systems . . . . .	218
Supplement No. 27	Interference from external sources . . . . .	218

---

NOTE

In this Fascicle, the expression "Administration" is used for shortness to indicate both a telecommunication Administration and a recognized private operating agency.