Additives for Polyolefins: Getting the Most Out of Polypropylene, Polyethylene, and TPO

Michael Tolinski



Table of Contents

| PF | REF/ | ACE | | | | | | | xiii |
|----|------|------------|--|------|------|------|------|------|------|
| | | | | | | | | | |

Section I: Overview of Polyolefins and Additives

| CHAPTER 1 | Intr | oduction | 3 |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|--------------------------------------------------------------------|----|
| | | Importance of POs | |
| | 1.2 | Importance of PO additives | 4 |
| | 1.3 | Recent issues in using additives | 5 |
| | | 1.3.1 Matching property requirements with additive type and amount | |
| | | 1.3.2 Doing more with less material | |
| | | 1.3.3 New properties for new markets | 7 |
| | | 1.3.4 Unintended additive interactions | 7 |
| | | 1.3.5 Faster processing | 8 |
| | | | |
| CHAPTER 2 | Trei | nds in Polyolefin and Additive Use | 9 |
| | 2.1 | PO market trends | 9 |
| | | 2.1.1 Growth vs. volatility | 10 |
| | | 2.1.2 Future resin growth and prices | 10 |
| a d'Al Alberta des La Alberta d | 2.2 | Overall trends in additives production and use | 11 |
| | 2.3 | Trends in resin compounding | 12 |
| a da fili general de la companya de la constante da Companya da constante da constant | 2.4 | Trends in specific PO applications | 13 |
| | | 2.4.1 Packaging trends | 14 |
| | | 2.4.2 Automotive trends for POs | |
| Carling and a second for the second se | | 2.4.3 Construction and infrastructure application | |
| 1946 - Lander Martin, Barrier († 1930) Den skiel stander († 1930) | | trends | 18 |

V

| Section II: | Environmental | Resistance |
|-------------|---------------|------------|
|-------------|---------------|------------|

| CHAPTER 3 | Antioxidants and Heat Stabilization |
|------------------|------------------------------------------------------------|
| | 3.1 Importance of AOs and stabilizers for POs |
| | 3.2 Primary and secondary AOs |
| | 3.2.1 Primary AOs (radical scavengers) |
| | 3.2.2 Secondary AOs (peroxide decomposers) |
| | 3.3 Factors determining AO selection |
| | 3.3.1 Thermal and color requirements in melt |
| | processing and in service |
| | 3.3.2 AO selection by PO type and finished product |
| | form |
| | 3.3.3 AO physical forms and handling |
| | 3.3.4 Synergies and antagonistic interactions |
| | 3.3.5 Cost40 |
| | 3.3.6 Environmental, food-contact, and health and |
| | safety considerations41 |
| | |
| CHAPTER 4 | Ultraviolet Light Protection and Stabilization |
| | 4.1 UV degradation of POs47 |
| | 4.2 UV blockers, screeners, and absorbers |
| | 4.2.1 UV-blocking and -absorbing fillers and pigments48 |
| | 4.2.2 Organic UV absorbers |
| | 4.3 Quenchers and peroxide decomposers |
| | 4.4 HALS: Free-radical scavengers |
| | 4.4.1 Overview of HALS51 |
| | 4.4.2 Interactions of HALS and other additives |
| | 4.5 Factors determining stabilizer selection |
| | 4.5.1 General factors |
| | 4.5.2 Light stabilizers for specific PO applications56 |
| | |
| CHAPTER 5 | Flame-Retarding Additives |
| | 5.1 Overview: The need for flame-retardant formulations 61 |
| | 5.1.1 Trends in flame-retarding additives61 |
| | 5.1.2 Mechanisms of burning62 |
| | 5.2 Halogen-based flame retardants |
| | 5.2.1 Composition of H-FRs64 |
| | 5.2.2 Concerns about halogenated FRs66 |
| | 5.3 Mineral-based flame retardants |
| | 5.3.1 ATH and MDH68 |
| | 5.3.2 Other mineral fillers' FR effects |

| | 5.4 | Intun | nescent and phosphorous-based flame retardants | s 70 |
|------------------|-----|--------|------------------------------------------------|------|
| | | 5.4.1 | Mechanisms of phosphorous FRs | 70 |
| | | 5.4.2 | Issues in improving phosphorous FRs | 71 |
| | 5.5 | | rs determining the selection of FR additives | |
| | | 5.5.1 | Cost, risk, and performance | 74 |
| | | 5.5.2 | Property effects and co-additive interactions | 75 |
| | | 5.5.3 | FR density and form | 76 |
| | | 5.5.4 | Halogen-free benefits (and costs) | 77 |
| | | | | |
| CHAPTER 6 | Ad | ditive | s for Modifying Electrical Properties | 79 |
| | 6.1 | | tatic and ESD additives | |
| | | 6.1.1 | Migrating chemical antistats | 81 |
| | | 6.1.2 | Nonmigrating polymers as permanent | |
| | | | antistatic/ESD additives | 85 |
| | | 6.1.3 | Conductive fillers as antistatic/ESD additives | 86 |
| | 6.2 | EMI s | shielding | 88 |
| | | 6.2.1 | Conductive fillers for EMI shielding | 88 |
| | | 6.2.2 | Conductive fibers for EMI shielding | 89 |
| | 6.3 | Choo | sing antistat/ESD/EMI additives | 89 |
| | | 6.3.1 | Antistat selection factors | 89 |
| | | 6.3.2 | Design considerations for EMI shielding | 90 |

Section III: Mechanical Property Enhancement

| CHAPTER 7 | Overview of Fillers and Fibers | 95 |
|-----------|----------------------------------------------|-----|
| | 7.1 Importance of fillers and fibers for POs | 96 |
| | 7.2 Common inorganic fillers | 96 |
| | 7.2.1 Calcium carbonate | 97 |
| | 7.2.2 Talc | |
| | 7.2.3 Wollastonite | |
| | 7.2.4 Mica | 100 |
| | 7.2.5 Silica | |
| | 7.2.6 Glass flour and spheres | |
| | 7.2.7 Other microfillers | |
| | 7.3 Nanofillers | |
| | 7.3.1 Potential of nanofillers | |
| | 7.3.2 Platy nanoclays | |
| | 7.3.3 Nanotubes | |
| | 7.3.4 POSS nanomaterials | |
| | 7.4 Impact modifiers and TPOs | |
| | 7.4.1 Impact modification for thick products | |
| | 7.4.2 Impact modification for film and sheet | |

| | 7.5 | Fiber 1 | einforcement | 110 |
|-----------|-----|---------|------------------------------------------|-----|
| | | 7.5.1 | Short glass fibers | 111 |
| | | 7.5.2 | Long glass fibers | 112 |
| | | 7.5.3 | Plant-based fibers | 115 |
| | | 7.5.4 | Other kinds of fiber reinforcement | 118 |
| CHAPTER 8 | | | etermining the Selection of Fillers | 101 |
| | | | | 121 |
| | 8.1 | | g costs and improving properties with | 122 |
| | 8.2 | Impac | t modification: Balancing stiffness with | |
| | | toughr | 1ess | 124 |
| | 8.3 | Mecha | nical reinforcement: Properties create | |
| | | opport | unities | 126 |
| | 8.4 | Proces | sing pitfalls and hidden costs | 128 |
| | 8.5 | Questi | ons when choosing fillers and fibers | 132 |

Section IV: Appearance Enhancement

| CHAPTER 9 | Col | lorants | | 139 |
|-------------------|------|---------|--------------------------------------------|-------|
| | 9.1 | Colori | ng strategies | .139 |
| | | 9.1.1 | White colorants | .140 |
| | | 9.1.2 | Black colorants | .141 |
| | | 9.1.3 | Full-spectrum colorants | .141 |
| | | 9.1.4 | Metallic colorants | .145 |
| | | 9.1.5 | Pearlescent colorants and color-enhancing | |
| | | | additives | . 147 |
| | 9.2 | Colora | nt delivery and processing | .148 |
| | | 9.2.1 | Colorant delivery | .148 |
| | | 9.2.2 | Processing issues with colorants | .150 |
| | 9.3 | Factor | s that affect the choice of colorant | .151 |
| | | 9.3.1 | General factors | .151 |
| | | 9.3.2 | Additive/colorant interactions | .155 |
| | | 9.3.3 | External coatings vs. internal colorants | .156 |
| | | | | |
| CHAPTER 10 | Nuc | leation | and Clarity | 157 |
| | 10.1 | Nuclea | ating agents: Overview | .157 |
| | | 10.1.1 | Nucleating agent effects on processing and | |
| | | | properties | .158 |
| | | 10.1.2 | Clarifying nucleating agents | .162 |

| 10.2 | Factor | s in choosing nucleating/clarifying agents | 164 |
|------|--------|--------------------------------------------|-----|
| | 10.2.1 | Applications and resins | 164 |
| | 10.2.2 | Practical use factors | 166 |

Section V: Processing Aids

| CHAPTER 11 | Proc | essing | Aids for Molding 171 |
|-------------------|------|---------|------------------------------------------------|
| | 11.1 | Melt-f | low modification and mold release171 |
| | | 11.1.1 | Melt-flow-enhancing lubricants and |
| | | | modifiers |
| | | 11.1.2 | Mold-release additives175 |
| | 11.2 | Specia | l cases for processing aids in molding177 |
| | | 11.2.1 | Aids for molding highly filled compounds 177 |
| | | 11.2.2 | Aids for ISBM178 |
| | | 11.2.3 | Aids for rotational molding179 |
| CHAPTER 12 | Proc | essing | Aids for Extrusion |
| | 12.1 | Requir | rements of extrusion-based processes |
| | 12.2 | Slip ag | jents |
| | 12.3 | Antibl | ocking agents184 |
| | | 12.3.1 | Inorganic antiblocks184 |
| | | 12.3.2 | Organic antiblocks186 |
| | | 12.3.3 | Clarity/slip antiblocks188 |
| | 12.4 | Additi | ves for reducing melt fracture and die |
| | | buildu | p |
| | | 12.4.1 | Fluoropolymer processing aids190 |
| | | 12.4.2 | Reducing die and screen-pack fouling191 |
| | 12.5 | | sing aids for specific extrusion situations191 |
| | | | High-throughput extrusion191 |
| | | | LLDPE blown-film stability192 |
| | | | Oriented PP slit tape fibrillation192 |
| | | | Thin PP fibers |
| | | | Highly filled masterbatch production193 |
| | | 12.5.6 | Wood-plastic composites193 |
| Section VI: | Oth | er Mo | difications of Form and Function |

| CHAPTER 13 | Reducing | Density: Polyolefin Foams | 197 |
|-------------------|------------|----------------------------------------|-----|
| | 13.1 Blowi | ng foams: External agents vs. internal | |
| | agent | s | |
| | 13.1.1 | Physical blowing agents | |
| | 13.1.2 | Chemical blowing agents | |

| | 13.2 | Produ | ct sectors requiring chemical | |
|------------|-------|----------|------------------------------------------------|------|
| | | blowiı | ng agents | 200 |
| | | 13.2.1 | Molded packaging and consumer products | s200 |
| | | 13.2.2 | Automotive moldings | 201 |
| | | 13.2.3 | Extruded construction products | 202 |
| | | 13.2.4 | Foaming in rotational molding | 202 |
| | 13.3 | Factor | s in blowing better foams | 203 |
| CHAPTER 14 | Cou | pling, | Compatibilizing, Recycling, and | |
| | Biod | legrad | ability | 205 |
| | 14.1 | Coupli | ing fillers and fibers with the PO matrix | 205 |
| | | 14.1.1 | Traditional coupling agents | 206 |
| | | 14.1.2 | Alternative coupling agents | 207 |
| | 14.2 | Compa | atibilizers for integrating regrind and recycl | ed |
| | | materi | als | 209 |
| | 14.3 | Additi | ves that promote PO biodegradability | 212 |
| CHAPTER 15 | Cros | slinkir | ng | 215 |
| | 15.1 | Crossl | inked PE: advantages and applications | 215 |
| | 15.2 | Crossl | inking agents | 217 |
| | | 15.2.1 | Peroxide-based agents | 217 |
| | | 15.2.2 | Silane-based agents | 218 |
| | | 15.2.3 | Radiation-induced crosslinking | 219 |
| | 15.3 | Factor | s in choosing crosslinking agents | 219 |
| CHAPTER 16 | Steri | lizatio | n and Radiation Resistance | 221 |
| | 16.1 | Steriliz | ation effects on PO products | 221 |
| | | 16.1.1 | Effects of irradiation sterilization | 221 |
| | | 16.1.2 | Effects of EtO sterilization | 223 |
| | | 16.1.3 | Effects of high-temperature sterilization | 223 |
| | 16.2 | Additi | ve solutions for sterilization-resistant POs | 223 |
| CHAPTER 17 | Aest | hetics | Enhancement and Surface | |
| | Mod | ificatio | n | 225 |
| | 17.1 | Anti-s | cratch additives | 226 |
| | | 17.1.1 | Conventional anti-scratch approaches | 226 |
| | | 17.1.2 | Evaluating anti-scratch additives | 227 |
| | | 17.1.3 | Alternative anti-scratch additives | 227 |
| | 17.2 | Antifo | gging agents | 228 |
| | 17.3 | Antim | icrobials and biocides | 229 |
| | 17.4 | Odor-n | nodifying additives | 231 |

•

Section VII: Conclusion: Incorporating Additives

| CHAPTER 18 | Adding Additives to Resin | | 235 |
|-------------------|---------------------------|--------------------------------------------|-----|
| | 18.1 | Handling additives | 235 |
| | | 18.1.1 Practical handling issues | 236 |
| | | 18.1.2 Health and safety issues | 236 |
| | 18.2 | Mixing and dispersing additives into resin | 237 |
| | | 18.2.1 Screw-processing developments | 237 |
| | | 18.2.2 "Lean" compounding | 238 |
| | 18.3 | Blending and feeding additives | 238 |
| | 18.4 | Choosing the best form of an additive | 239 |
| REFERENCES | | | 243 |
| INDEX | | | 275 |