

Fraunhofer-Institut für  
Hochfrequenzphysik und Radartechnik FHR

Robert Kohlleppel

Ground moving target tracking with  
space-time adaptive radar

FRAUNHOFER VERLAG

# Contents

<b>1</b>	<b>Introduction</b>	<b>13</b>
<b>2</b>	<b>Fundamentals of ground moving target indication</b>	<b>19</b>
2.1	Airborne MTI radar	19
2.2	The radar signal	23
2.3	Data processing and target detection	26
2.4	Signal model	29
2.5	Space time adaptive processing	31
2.5.1	Fully adaptive space time processing	31
2.5.2	Partially adaptive space time processing	32
2.5.3	Performance of STAP	34
2.5.4	Parameter estimation	36
<b>3</b>	<b>Ground moving target indication and geolocation</b>	<b>37</b>
3.1	Application of space time adaptive processing to a received data set	40
3.1.1	Signal model of the received data set	40
3.1.2	Data preprocessing	42
3.1.3	Target detection with adjacent bin post Doppler processing	43
3.2	Parameter estimation	45
3.2.1	Target radial velocity	45
3.2.2	Target range	46
3.2.3	Direction of arrival estimation	46
3.3	Geolocation of detections	48
3.3.1	Geolocation of the detections with a plane earth assumption	49
3.3.2	Conversion of the Doppler measurement with a plane earth assumption	50
3.3.3	Geolocation with a digital elevation model	51
<b>4</b>	<b>Fundamentals of target tracking</b>	<b>55</b>
4.1	Probability Hypothesis Density Filter	59
4.2	Gaussian Mixture Probability Hypothesis Density Filter	61
<b>5</b>	<b>Ground moving target tracking algorithm</b>	<b>65</b>
5.1	Basic design choices	66
5.2	Modifications of the standard GM-PHD filter	67
5.2.1	State dependent detection probability	67
5.2.2	Association between detections and components	69
5.2.3	Merging with the Kullback-Leibler divergence	70
5.2.4	Ancestor relation	71
5.2.5	Immediate deletion of missed detection birth component descendants	73
5.2.6	Component fingerprints	74
5.2.7	Visualization of the GM-PHD filter results	76
5.2.8	Track extraction	77

5.3	Ground moving target tracking specific adaptations of the GM-PHD . . . . .	77
5.3.1	Definition of the target state space . . . . .	77
5.3.2	State propagation . . . . .	81
5.3.3	Definition of the measurement space . . . . .	82
5.3.4	Definition of the observation process . . . . .	83
5.3.5	Jacobians of the observation process . . . . .	86
5.3.6	Modeling of the state dependent probability of detection . . . . .	87
5.3.7	An expression for the false alarm probability . . . . .	89
5.4	Use of a digital elevation model . . . . .	91
5.4.1	Conversion from an ENU state to a track state . . . . .	92
5.4.2	Conversion from a track state to an ENU state . . . . .	92
5.4.3	Error propagation . . . . .	92
<b>6</b>	<b>Tracking results with simulated data</b>	<b>93</b>
6.1	Simulation of ground moving target detections by an airborne radar . . . . .	93
6.2	Tracking results with simulated scenarios . . . . .	96
6.2.1	Scenario 1 . . . . .	97
6.2.2	Scenario 2 . . . . .	99
6.2.3	Scenario 3 . . . . .	100
6.3	Example of the direct visualization of GM-PHD filter results . . . . .	104
6.4	Summary . . . . .	105
<b>7</b>	<b>Experimental results</b>	<b>107</b>
7.1	Acquisition of the dataset . . . . .	107
7.2	Target detections . . . . .	113
7.3	Tracking results . . . . .	114
<b>8</b>	<b>Tracking with signal adaptive measurement error covariance matrix</b>	<b>119</b>
8.1	Proposed model for the direction of arrival measurement error . . . . .	120
8.2	Experimental validation of the direction of arrival measurement error model . . . . .	121
8.2.1	Association between detections and ground reference vehicles . . . . .	124
8.2.2	Deviation of the radar and GPS based DOA measurements . . . . .	125
8.2.3	Variance of the deviation between the DOA estimates . . . . .	125
8.2.4	Experimental results . . . . .	126
8.3	Tracking with measurement covariance matrix adaptation . . . . .	130
8.4	Simulation results . . . . .	130
8.5	Tracking results with experimental data . . . . .	133
<b>9</b>	<b>Conclusion</b>	<b>143</b>
<b>A</b>	<b>Algorithms</b>	<b>145</b>
A.1	Geolocation of a target . . . . .	147
A.1.1	Function for the geolocation based on target range and directional cosine . . . . .	147
A.1.2	Jacobian of the geolocation function . . . . .	150
A.1.3	Function for selecting one solution of the possible target geolocations . . . . .	152
A.1.4	Function for a unique solution for the geolocation of the target . . . . .	153
A.2	Measurable velocity component . . . . .	153
A.2.1	Function for the measurable velocity component of a target constrained to a plane . . . . .	153
A.2.2	Jacobian of the measurable velocity with respect to the ENU parameters . . . . .	155

A.2.3	Determine a unique solution for the surface velocity component: $\mathbf{f}^{v \leftarrow \text{urv}}$	157
A.3	Range, radial velocity and directional cosine of a target	157
A.3.1	Function $\mathbf{f}^{\text{urv} \leftarrow \mathcal{E}}$	157
A.3.2	Jacobian of $\mathbf{f}^{\text{urv} \leftarrow \mathcal{E}}$	158
A.4	Clutter Doppler frequency versus range and directional cosine	160
A.5	Functions that are used by the tracking algorithm	161
A.5.1	Radar measurement to track measurement conversion: $\mathbf{f}^{\mathcal{M} \leftarrow \text{urv}}$	161
A.5.2	Definition of the measurement function: $\mathbf{h}_k$	161
A.5.3	Track measurement based on target state including measurement errors: $\mathbf{f}_\epsilon^{\mathcal{M} \leftarrow \mathcal{S}}$	162
A.5.4	Track measurement based on the track state without effect of measurement noise: $\mathbf{f}_0^{\mathcal{M} \leftarrow \mathcal{S}}$	162
A.5.5	Conversion of a location from 2 to 3 dimensions: $\mathbf{f}_p^{3 \leftarrow 2}$	163
A.5.6	Conversion of a velocity vector from 2 to 3 dimensions: $\mathbf{f}_v^{3 \leftarrow 2}$	164
A.5.7	Conversion of a 3d location to 2 dimensions: $\mathbf{f}^{2 \leftarrow 3}$	164
A.5.8	Conversion of a 3d velocity vector to 2 dimensions: $\mathbf{f}^{P2 \leftarrow \mathcal{E}}$	165
A.5.9	Locate a target in the tracking plane based on range and DOA measurement	165
A.5.10	Radar measurements based on track state: $\mathbf{f}^{\text{urv} \leftarrow \mathcal{S}}$	165
A.5.11	Radar measurement based on track measurement: $\mathbf{f}^{\text{urv} \leftarrow \mathcal{M}}$	166
A.6	Jacobians of functions that are used by the tracking algorithm	167
A.6.1	Jacobian of the functions that converts a 3d location to a 2d location	167
A.6.2	Jacobian of the function that converts the range Doppler measurement to a location in the tracking plane	168
A.6.3	Jacobian of the function that converts the radar measurement to the track input measurement	168
A.6.4	Jacobian of the track measurement with respect to measurement noise	169
A.6.5	Jacobian of the synthetic measurement with respect to the track state in the absence of noise	170
A.6.6	Jacobian of the radar measurements with respect to the track state	171
A.6.7	Jacobian of the radar measurement with respect to the track measurement	172
A.7	Other functions	173
A.7.1	Euler rotation matrix	173
A.7.2	Inverse Euler rotation matrix	174
A.7.3	Bilinear interpolation	174
A.8	Conversions with a digital elevation model	175
A.8.1	Mapping from the planar location to ENU location	175
A.8.2	Mapping from the track velocity to ENU velocity	176
A.9	Jacobians of the conversion between ENU and track coordinate systems	177
A.9.1	Jacobian of the location conversion with respect to the location	177
A.9.2	Jacobian of the location conversion with respect to the DEM model parameters	177
A.9.3	Jacobian of the location conversion with respect to track state and DEM model parameters	178
A.9.4	Jacobian of ENU velocity with respect to the DEM parameters	179
A.9.5	Jacobian of ENU velocity with respect to the track location	179
A.9.6	Jacobian of ENU velocity with respect to the track velocity	180
A.9.7	Jacobian of the ENU velocity with respect to the entire track state and the DEM parameters	180
A.9.8	Jacobian of entire ENU state with respect to the entire track state and the DEM parameters	181