

Table of Contents

1	Introduction.....	1
2	General code features	3
2.1	Code basis.....	3
2.2	Major code versions.....	3
2.3	Differences between TOUGH2 and TOUGH2-MP	5
2.4	Deviations from TOUGH2 and TOUGH2-MP defaults.....	6
2.4.1	Unlimited number of materials (only TOUGH2-GRS).....	6
2.4.2	Unlimited number of time steps.....	6
2.4.3	Automatic Leverett scaling disabled.....	7
2.4.4	Extended printouts.....	7
2.4.5	Conservation of floating point precision (only TOUGH2-GRS).....	7
2.4.6	Enforced solution of linear equations	8
2.5	Modules and physical processes	8
2.6	Handling porosity changes.....	11
2.7	Handling permeability changes.....	13
2.8	Restarting	13
3	New flow and transport features	17
3.1	Check valve boundary (IRP=9 in combination with an upstream weighting of mobilities).....	17
3.2	Simulated vertical pressure gradient (ICP=9 with IRP=1).....	17
4	CNTRL: Simulation controls	21
4.1	Termination controls	21
4.1.1	Do not exit on equilibrium (obsolete).....	21
4.1.2	Minimum time step width	21

4.2	Time step controls	22
4.2.1	Incrementing step widths	22
4.2.2	Avoiding convergence failures	22
4.2.3	Avoiding small time steps before printout times	22
4.2.4	Avoiding large changes in gas generation	23
4.3	Output controls	23
4.3.1	Precision of time series printouts	23
4.3.2	Reducing the amount of time series printouts	23
4.4	Input data	24
5	COMP: Convergence and compaction	25
5.1	Physical models.....	25
5.1.1	Change of cavity volume and porosity	25
5.1.2	Compaction rates.....	26
5.2	Note on the compaction of saturated media.....	28
5.3	Input data	28
6	CORFL	31
6.1	Implementation	31
6.2	Source and sink calculation	32
6.3	Degree of corrosion	33
6.4	Permeability change	34
6.5	Input data	35
7	CORRO: Gas production due to iron corrosion	37
7.1	Water consumption.....	37
7.2	Gas component	38
7.3	Gas generation rates	41
7.4	Input data	44

8	DEGRA: Time-dependent permeability changes	47
8.1	Model and implementation	47
8.2	Input data	47
9	DOFT.....	49
10	FISS: Gas pathway dilation	51
10.1	Pressure thresholds and softening models	51
10.2	Fissure porosity models	52
10.3	Permeability models	53
10.4	Input data	55
11	GCOMP: Primary non-condensable gas component	57
11.1	Absolute molecular weight	57
11.2	Specific enthalpy.....	57
11.3	Inverse Henry constant.....	58
11.4	Gas phase viscosity.....	58
11.5	Input data	60
12	PRLIM: Gas pressure limitation.....	61
12.1	Model and implementation	61
12.2	Input data	62
13	PTIME: High-precision printout times	63
14	RANGE: Limiting primary variables	65
14.1	Limiting brine mass fraction	65
14.2	Constant brine mass fraction	66

14.3	Clipping gas saturation and reducing vapour pressure	66
14.4	Input data	68
15	RELA: permeability and capillary pressure functions	69
15.1	Porosity-permeability relationships	69
15.2	Change of capillary pressures.....	69
15.3	Temperature-dependent capillary pressures.....	70
15.4	Input data	70
16	RN	73
16.1	Links to standard TOUGH2.....	73
16.2	Time stepping and performance	73
16.3	Simulation controls	75
16.4	Decay and adsorption of Nuclides	75
16.5	Anion exclusion	76
16.6	Extended mobilization models	79
16.6.1	New commands.....	79
16.6.2	Canister failure models	80
16.6.3	Bond models.....	83
16.6.4	Implementation	83
16.7	Input data	84
17	Output.....	87
17.1	Global printouts for elements (ELE_MAIN)	87
17.2	Global printouts for connections (CON_MAIN).....	90
17.3	Time series for elements (FOFT).....	92
17.4	Time series for connections (COFT)	94
17.5	Time series for sinks and sources (GOFT).....	95

17.6	Time series for domains (DOFT).....	96
	References	97
	List of Figures.....	103
	List of Tables	105
	Acknowledgements	107