

Table of Contents

Danksagung	III
List of Figures.....	V
List of Tables	VIII
1 Introduction.....	1
2 Theoretical background.....	5
2.1 Physical and chemical background	5
2.1.1 Basics of radioactive decay	5
2.1.2 Modes of radioactive decay	6
2.1.3 Statistics of radioactive decay	8
2.1.4 Physical and chemical properties of radon	10
2.2 Geological background.....	14
2.2.1 Radon as part of the natural decay chains	14
2.2.2 Radon as an omnipresent component of groundwater.....	15
2.2.3 Radon migration in groundwater.....	20
2.3 Applicability of radon as a natural geochemical tracer for study of groundwater discharge into lakes	26
3 On-site techniques for determination of radon in water	28
3.1 Continuous and discrete on-site ex-situ determination of radon in ground- and surface waters	28
3.1.1 Introduction	28
3.1.2 Material.....	29
3.1.3 Laboratory and field experiments.....	30
3.1.3.1 Continuous measurements	31
3.1.3.2 Measurement of discrete samples	32
3.1.4 Results and discussion	33
3.1.4.1 Continuous measurements	33
3.1.4.2 Measurement of discrete samples	35
3.1.5 Conclusion	38
3.2 Continuous on-site in-situ determination of radon in surface waters.....	39
3.2.1 Introduction	39
3.2.2 Methodology.....	39
3.2.2.1 Equipment setup.....	39
3.2.2.2 Detection limit, data reproducibility, and response time	41
3.2.3 Experimental.....	43
3.2.3.1 Influence of selected membrane properties and membrane dimensions	43
3.2.3.2 Test of the radon extraction module	46
3.2.4 Results and discussion	50
3.2.4.1 Influence of selected membrane properties and membrane dimensions	50
3.2.4.2 Test of the radon extraction module	54

3.2.5	Conclusion	57
4	Application of radon for tracing groundwater discharge into lakes.....	58
4.1	Using radon for tracing groundwater discharge into a meromictic lake.....	58
4.1.1	Introduction.....	58
4.1.2	Basic concept	58
4.1.3	Study area.....	63
4.1.4	Material and Methods	65
4.1.4.1	Sampling.....	65
4.1.4.2	Methods used.....	65
4.1.5	Results and discussion	67
4.1.5.1	pH, electrical conductivity, and temperature depth profiles	67
4.1.5.2	Excess radon profiles.....	68
4.1.5.3	Radon activity concentration of the discharging groundwater.....	70
4.1.5.4	Diffusive benthic fluxes	71
4.1.5.5	Atmospheric evasion	73
4.1.5.6	Radon budget and estimation of groundwater discharge	73
4.1.6	Conclusion	75
4.2	Using radon for tracing groundwater discharge into a dimictic lake.....	76
4.2.1	Introduction.....	76
4.2.2	Study area.....	76
4.2.3	Material and Methods	77
4.2.3.1	Modeling approach.....	77
4.2.3.2	Sampling and measurement.....	78
4.2.3.3	Hydrologic studies based on Darcy's law	79
4.2.4	Results and discussion	80
4.2.4.1	pH, electrical conductivity, and temperature depth profiles	80
4.2.4.2	Excess radon profiles.....	81
4.2.4.3	Radon activity concentration of the discharging groundwater.....	83
4.2.4.4	Diffusive benthic fluxes	84
4.2.4.5	Atmospheric evasion	85
4.2.4.6	Radon budget and estimation of groundwater discharge	85
4.2.5	Summary and Conclusion	89
5	Conclusions for the use of radon as a natural geochemical tracer for study of groundwater discharge into lakes	90
	Bibliography	92

List of Figures

Figure 2-1:	Gaussian distribution with specific confidence intervals (Turner 2007, modified).	10
Figure 2-2:	Schematic illustration of emanation processes (Tanner 1980, modified).	19
Figure 3-1:	Schematic sketch of the experimental setup for continuous radon-in-water measurement.	31
Figure 3-2:	Schematic sketch of the experimental setup for radon measurement in discrete water samples.	32
Figure 3-3:	Comparison of radon-in-water activity concentrations at different water flow rates. Open circles label the extraction cell, black squares the RADAqua results.	34
Figure 3-4:	Comparison of results achieved with extraction cell and RADAqua for radon activity concentrations along a transect through a harbour area off Bremerhaven.	35
Figure 3-5:	Polonium-218 count rates for different water sample volumes. For each measurement radon-in-water activity concentrations and circling air volumes are the same.	37
Figure 3-6:	a) Radon extraction module; b) scanning electron microscope image of the membrane material (photo by Membrana).	41
Figure 3-7:	Experimental setup for varying radon activity concentration in the donor phase; the air stream is indicated by arrows.	44
Figure 3-8:	Experimental setup for inversion of radon transport direction; the air stream is indicated by arrows.	46
Figure 3-9:	Temperature dependence of $k_{w/air}$	49
Figure 3-10:	Increase in radon activity concentration as $f(t)$ for six different concentration levels; the experiment with 30 kBq m^{-3} was carried out twice.	50
Figure 3-11:	Increase in radon activity concentration as $f(t)$; mean values of the data sets displayed in Figure 3-10.	51
Figure 3-12:	Increase in radon activity concentration as $f(t)$ for six different lengths of the membrane tubing.	52

Figure 3-13: Decrease in radon activity concentration as $f(t)$ (mean values from four experiments)	53
Figure 3-14: Increase in radon activity concentrations as $f(t)$ in four steps; activity concentrations determined by LSC are also given partitioning.	54
Figure 3-15: Decrease in radon activity concentration as $f(t)$	56
Figure 3-16: Radon activity concentrations in four depths in a lake determined by means of the radon extraction module.	57
Figure 4-1: Simple box model showing possible input and output terms supporting the radon inventory of a lake water body; F_{adv} -input is the desired result of this study.	59
Figure 4-2: a) Location of the study area; b) Lake Waldsee with groundwater wells (WS) and lake water sampling points (SP); dashed lines indicate contour lines of lake water depth [m]. Stars show sediment sampling points: < 2 m depth = MIX 1, > 2 m depth = MON 1 – 4, with increasing numbers from SE to NW.	64
Figure 4-3: Depth profiles of pH, electrical conductivity, and temperature at sampling point SP 2 during a) the October and b) the December 2006 sampling.	68
Figure 4-4: Excess radon depth profiles determined during the two sampling campaigns.....	70
Figure 4-5: Sediment surface area [m^2] vs. water volume [m^3] as a function of depth.....	72
Figure 4-6: a) Location of the investigation area; b) Lake “Ammelshainer See” with sampling points (SP); drawn through line indicates lake boundary, dashed lines indicate contour lines of lake water depth [m]....	77
Figure 4-7: Representative vertical profiles of pH, temperature, and electrical conductivity measured during (a) April and (b) May 2007 at SP 4 (cf. Figure 4-6b).	81
Figure 4-8: Excess radon depth profiles at each sampling point during the April campaign. Uncertainties are at the 2σ level and based on counting statistics.....	82

Figure 4-9: Excess radon depth profiles at each sampling point during the May campaign. Uncertainties are at the 2σ level and based on counting statistics.	82
---	----

List of Tables

Table 2-1:	Properties of radon-222 under standard state (T = 273.15 K, p = 101 325 Pa; Weigel 1978, Stein 1983, Cothorn 1987, Wilkening 1990).	11
Table 2-2:	Hildebrand parameter (δ) of selected liquid phases and their partition coefficients ($k_{w/air}$) at 25°C (Barton 1991).	13
Table 2-3:	Selected members of the naturally decay chains of uranium-238, thorium-232, and uranium-235, their respective half-lives, and decay modes. The short-lived radon progeny is marked in grey (Schubert 2006, modified).	14
Table 2-4:	Mean specific radium-226 activities of rock species (Nazaroff et al. 1988).	16
Table 2-5:	Emanation coefficient (ϵ) of mineral materials.....	17
Table 3-1:	Comparison of equilibrium activity concentrations achieved with extraction cell and RADAqua; uncertainties (2 σ -error) are based on counting statistics.....	34
Table 3-2:	Comparison of extraction cell results and RADAqua results for water samples taken from different sites in Germany.	37
Table 4-1:	Excess radon inventories and total benthic radon fluxes ($F_{total} = F_{adv} +$ F_{diff}) determined in the mixolimnion (MIX) and the monimolimnion (MON) during the two sampling campaigns.....	70
Table 4-2:	Radon activity concentrations determined during batch experiments with sediment samples taken from the mixolimnion (MIX) and the monimolimnion (MON) and respective diffusive radon fluxes.....	72
Table 4-3:	Parameters used for calculations to estimate groundwater discharge into Lake Waldsee in October and December 2006.	74
Table 4-4:	Input and output fluxes of radon for Lake Waldsee.....	74
Table 4-5:	Average excess radon activity concentrations for the water columns at each sampling point and resulting excess radon inventories (based on the average water depth of about 10 m) during the April sampling campaign.	83
Table 4-6:	Average excess radon activity concentrations for the water columns at each sampling point and resulting excess radon inventories (based on	

the average water depth of about 10 m) during the May sampling campaign.....	83
Table 4-7: Measured specific radium-226 activities of lake sediments and calculated benthic diffusive fluxes.	85
Table 4-8: Radon fluxes and groundwater (GW) discharge rates for the April and May sampling campaign. As radon activity concentration for the groundwater endmember $316 \pm 12.9 \text{ Bq m}^{-3}$ was used (cf. section 4.2.4.3). Note: $\lambda_{222}I_{222}$ represents the decay of the total radon activity concentration.	87
Table 4-9: Groundwater discharge and lake water residence times for the April and May sampling campaign.....	88