

Contents

List of Acronyms	xiii
List of Figures	xxi
List of Tables	xxxv
Preface	xxxvii
Acknowledgments	xxxix
List of Contributors	xli

1 Introduction	1
<i>Cedric F. Lam</i>	
1.1 History of Broadband Access Networks and PON	1
1.1.1 Digital Subscriber Line (DSL)	2
1.1.2 Cable Modem	3
1.1.3 Fiber Access Systems	7
1.1.4 Ethernet	8
1.1.5 WDM in Optical Access Networks	11
1.1.6 Killer Applications	11
1.2 Economic Considerations in PON Development	12
1.2.1 How Much Bandwidth Is Enough?	12
1.2.2 Policy and Regulation Influence	13
1.2.3 Standardization Efforts	14
1.2.4 Cost Considerations	14
1.3 Organization of the Book	15
References	16

2 PON Architectures Review	19
<i>Cedric F. Lam</i>	
2.1 FTTx Overview	19
2.2 TDM-PON vs WDM-PON	20
2.3 Optical Transmission System	21
2.3.1 Optical Fiber	21
2.3.2 Chromatic Dispersion	23
2.3.3 Fiber Loss	25

2.3.4	Bidirectional Transmission	26
2.3.5	Wavelength Division Duplex	27
2.4	Power-Splitting Strategies in a TDM-PON	29
2.4.1	Splitting Architectures	29
2.4.2	Splitting Ratio	30
2.5	Standard Commercial TMD-PON Infrastructure	30
2.5.1	OLT and ONU Structures	31
2.5.2	Burst Mode Operation and Ranging	33
2.5.3	C-Band Analog CATV Signal Overlay	35
2.5.4	Security Concerns in Power-Splitting PON	36
2.6	APON/BPON and G-PON	37
2.6.1	ATM-PON and ITU-T G.983	37
2.6.2	Collision Resolution in APON/G-PON	42
2.6.3	Wavelength Overlay in APON/G-PON	42
2.6.4	G-PON and ITU-T G.984	43
2.6.5	APON/G-PON Protection Switching	54
2.7	EPON	54
2.7.1	Ethernet Layering Architecture and EPON	54
2.7.2	EPON PMD Layer	56
2.7.3	Burst Mode Operation and Loop Timing in EPON	56
2.7.4	PCS Layer and Forward Error Correction	59
2.7.5	Ethernet Framing	59
2.7.6	Multipoint Control Protocol (MPCP)	60
2.7.7	Point-to-Point Emulation (P2PE) in EPON	65
2.7.8	EPON Encryption and Protection	67
2.7.9	Ethernet OAM Sublayer	68
2.8	G-PON and EPON Comparison	69
2.9	Super PON	70
2.10	WDM-PON	71
2.10.1	Advantages and Challenges of WDM-PON	72
2.10.2	Arrayed Waveguide Grating (AWG) Router	72
2.10.3	Broadcast Emulation and Point-to-Point Operation	74
2.10.4	2-PONs-In-1	74
2.10.5	WDM-on-WDM	75
2.10.6	Hybrid WDM/TDM-PON	76
2.10.7	Multiply Fiber Plant Utility by WDM	80
2.11	Summary	84
	References	84

3 Optical Technologies in Passive Optical Access Networks **87**

Elaine Wong

3.1	Introduction	87
3.2	Optical Technologies in Passive Outside Plant	91

3.2.1	Planar Lightwave Circuit (PLC)-Based Optical Power Splitter	91
3.2.2	Arrayed Waveguide Grating	93
3.3	PON Technologies for Indoor Installation	108
3.3.1	Field Assembly and Indoor Connectors	108
3.3.2	Fiber for Indoor Installations	112
3.4	Transmitter Sources at Subscriber Premises	120
3.4.1	Introduction	120
3.4.2	Wavelength-Specific ONUs	122
3.4.3	Colorless ONUs	129
3.4.4	Source-Free ONUs Based on Wavelength Reuse Schemes	137
3.5	Summary	141
	References	143
4	Transceivers for Passive Optical Networks	151
	<i>Yongmao Frank Chang and Badri Gomatam</i>	
4.1	Introduction	151
4.1.1	Historical Background	152
4.1.2	PON Transceiver Evolution	153
4.2	PON System Requirements	154
4.2.1	PON System Power Budgets and Specifications	154
4.2.2	Physical-Layer Specifications	155
4.2.3	PON Burst-Mode Timing Requirements	156
4.3	Transceiver Technologies	161
4.3.1	Transceiver Building Blocks	162
4.3.2	Optical Transmit and Receive Devices	163
4.3.3	Bidirectional Optical Subassembly (BOSA)	167
4.3.4	PON Transceiver Modules	172
4.4	Burst-Mode Electronics	174
4.4.1	Conventional vs Burst-Mode Data	174
4.4.2	Burst-Mode Transmitter (BM Tx)	175
4.4.3	Burst-Mode Receiver (BM Rx)	181
4.5	Transceiver Digital-Diagnostic Monitoring	187
4.5.1	Module Parameter Monitoring	188
4.5.2	Fiber OTDR Monitoring	192
4.6	PON Transceiver System Evaluation	196
4.6.1	G-PON Transceiver System Evaluation	197
4.6.2	EPON Transceivers	202

4.6.3	Impact of Analog CATV Overlay	205
4.7	Summary and Outlook	207
	References	209
5	Ranging and Dynamic Bandwidth Allocation	215
	<i>Noriki Miki and Kiyomi Kumozaki</i>	
5.1	Ranging	215
5.1.1	Purpose of Ranging	215
5.1.2	Ranging Procedures Overview	216
5.1.3	Ranging Protocol of G-PON	218
5.1.4	Ranging Protocol of EPON	220
5.2	Dynamic Bandwidth Allocation (DBA)	221
5.2.1	DBA Overview	221
5.2.2	Target Service	222
5.2.3	Requirements of DBA	224
5.2.4	Traffic Control Fundamentals—Fair Queuing	226
5.2.5	IPACT and its Variants	228
5.2.6	Improved DBA	231
	References	241
6	Protection Architectures for Passive Optical Networks	243
	<i>Calvin C. K. Chan</i>	
6.1	Introduction	243
6.2	Considerations of Protection in Passive Optical Networks	244
6.2.1	Protection or Restoration	245
6.2.2	Network Topology	245
6.2.3	Network Type	246
6.2.4	Resources To Be Protected	246
6.2.5	Single or Multiple Failures	247
6.2.6	Automatic Protection Switching	247
6.2.7	Operation, Administration, and Management	247
6.2.8	Traffic Restoration Time	247
6.2.9	Complexity	248
6.3	Protection Architectures	248
6.3.1	Conventional Passive Optical Networks	248
6.3.2	WDM Passive Optical Networks	253
6.4	Summary	261
	Acknowledgments	264
	References	264

7 Optical Characterization, Diagnosis, and Performance Monitoring for PON	267
<i>Alan E. Willner and Zhongqi Pan</i>	
7.1 Introduction	267
7.2 Network Testing, Characterization, and Monitoring Challenges for PON	269
7.2.1 Fiber's Key Characteristics	269
7.2.2 Characterization and Monitoring Challenges for PON	271
7.3 Methods for Characterization, Diagnosis, and Monitoring	275
7.3.1 Required Physical-Layer Measurement	275
7.3.2 Basic Test Equipment	275
7.3.3 Network Testing, Characterization, and Diagnosis Guidelines	277
7.3.4 Network Performance Monitoring	278
7.4 Conclusion	296
Acknowledgments	296
References	296
Appendix I G-PON PMD Characteristics	301
Appendix II EPON MPCPDU Formats	311
Index	315

List of Figures

Figure 1.1	Development trend of Ethernet technologies.	9
Figure 2.1	Generic structure of a modern telecommunication network.	20
Figure 2.2	FTTx alternatives (from [1]).	21
Figure 2.3	Architecture of (a) TDM-PON and (b) WDM-PON.	22
Figure 2.4	Single-mode fiber (SMF) vs multimode fiber (MMF).	23
Figure 2.5	Dispersion coefficient as a function of wavelengths for various types of optical fibers.	24
Figure 2.6	Loss in an optical fiber at different wavelengths.	25
Figure 2.7	(a) One-fiber single-wavelength bidirectional transmission. (b) Near-end cross talk (NEXT).	27
Figure 2.8	Wavelength division duplex uses 1.3/1.5- μm coarse WDM coupler (diplexer) to separate upstream and downstream signals.	28
Figure 2.9	Splitting strategies in a TDM-PON: (a) one-stage splitting, (b) multistage splitting, and (c) optical bus.	29
Figure 2.10	Standard commercial TMD-PON architecture.	31
Figure 2.11	Generic structure of a standard TDM-PON OLT. This diagram represents a chassis with multiple OLT cards, which are interconnected through a back plane switch. Each OLT card with its own MAC and PMD layer serves a separate PON.	32
Figure 2.12	Generic structure of a standard TDM-PON ONU.	33
Figure 2.13	Overlaying analog broadcast TV services on a TDM-PON using the 1.55- μm wavelength.	36
Figure 2.14	Downstream and upstream APON frame formats at 155.52-Mbps speed. For 622.08-Mbps and 1244.16-Mbps speed, the numbers of time slots are simply multiplied by 4 and 8 to the numbers shown in the above diagrams.	39
Figure 2.15	ATM switching examples: (a) VP and VC switching and (b) VC switching.	41
Figure 2.16	Wavelength allocation plan in ITU-T G.983.3.	43
Figure 2.17	A T-CONT represent a logical link between the OLT and an ONU.	45

Figure 2.18	ATM-based T-CONT vs GEM-based T-CONT.	46
Figure 2.19	Protocol stack of the G-PON transmission convergence (GTC) layer (from [24]).	46
Figure 2.20	GTC downstream signal consists of 125- μ s frames with a PCBd header and a payload section.	48
Figure 2.21	GTC downstream frame and media access control concept (from [24]).	48
Figure 2.22	GTC downstream frame formats.	49
Figure 2.23	GTC upstream framing: each ONT starts the upstream transmission with PLOu. An ONT assigned with two Alloc-ID in two consecutive upstream allocations only needs to transmit PLOu once.	50
Figure 2.24	GTC upstream frame format.	51
Figure 2.25	GEM frames in upstream payload (from [24]).	52
Figure 2.26	GEM encapsulation formats.	52
Figure 2.27	Mapping and fragmentation of user data frames into GEM payload (from [24]).	53
Figure 2.28	Multiplexing of urgent data using GEM fragmentation process (from [24]).	54
Figure 2.29	Point-to-point (P2P) Ethernet and point-to-multipoint (P2MP) EPON layering architecture.	55
Figure 2.30	Standard Ethernet frame format.	60
Figure 2.31	EPON ranging process.	61
Figure 2.32	EPON Gate operation.	62
Figure 2.33	EPON Report operation.	63
Figure 2.34	Generic format of MPCPDU.	63
Figure 2.35	Autodiscovery process (from [9]).	64
Figure 2.36	Although all the ONU traffic arrives at the same physical port at the OLT, because of the directional power-splitting coupler used at the remote node, ONUs cannot see each other's traffic without the forwarding aid of OLT.	66
Figure 2.37	Point-to-point emulation in EPON.	66
Figure 2.38	Modified preamble with LLID for point-to-point emulation in EPON.	67
Figure 2.39	EPON point-to-point emulation operation.	68
Figure 2.40	Point-to-point and single-copy broadcast (SCB) MACs in an EPON model.	68
Figure 2.41	Conventional WDM coupler vs arrayed waveguide grating.	73
Figure 2.42	Emulation of broadcast services on a WDM-PON with a broadband source.	74

Figure 2.43	A modified AWG for 2-PONs-in-1.	75
Figure 2.44	By using CWDM devices to combine and separate optical signals in multiple FSRs of an AWG device, a highly flexible WDM-on-WDM system can be achieved.	76
Figure 2.45	Split-net test-bed demonstrating the WDM-on-WDM concept (from [50]).	77
Figure 2.46	Demonstration of a hybrid WDM/TDM-PON with wavelength-selection-free transmitters: (a) downstream link and (b) upstream link (from [52]).	78
Figure 2.47	WE-PON optical layer block diagram. (Courtesy of ETRI and Korea Telecom.)	79
Figure 2.48	RSOA module used in ETRI WE-PON prototype. (Courtesy of ETRI and Korea Telecom.)	80
Figure 2.49	Feed-forward current injection to RSOA in WE-PON. (Courtesy of ETRI and Korea Telecom.)	81
Figure 2.50	PLC-ECL used in WE-PON prototype. (Courtesy of ETRI and Korea Telecom.)	82
Figure 2.51	A band sorter interleaves the optical spectrum into bands (top) which can be further separated with diplexers (bottom) into bands for upstream and downstream PON connections.	83
Figure 2.52	Overlaying APON and EPON on the same fiber plant using “band sorters.”	83
Figure 3.1	A PLC splitter is manufactured using two fiber arrays and one PLC chip all aligned within one package. (From Ref [1])	91
Figure 3.2	Measured insertion loss of a 1×32 PLC splitter as a function of wavelength, showing uniform insertion loss (≤ 1.25 -dB variation) and low excess insertion loss (≤ 1.25 dB) above the theoretical value. (From Ref [3])	92
Figure 3.3	Schematic illustration of arrayed waveguide grating comprising two free-propagating regions and a waveguide array. (From Ref [7])	94
Figure 3.4	Schematic layout of $N \times N$ arrayed waveguide grating router. (From Ref [12])	95
Figure 3.5	Schematic illustration of the cyclic property of an arrayed waveguide grating router. (From Ref [12])	95
Figure 3.6	Schematic illustration of dual-function reflective arrayed waveguide grating. (From Ref [13])	96

Figure 3.7	(a) Fiber-to-fiber insertion loss of 1×14 power splitter function; (b) transmission spectra of 14-channel wavelength-router function. (From Ref [13])	97
Figure 3.8	Schematic illustration of 1×8 two-PONs-in-one (2P1) device. For clarity, the vertical scale has been expanded by four times. (From Ref [14])	98
Figure 3.9	Spectra from the output ports of a 1×8 2P1 device measured around the (a) $1.3\text{-}\mu\text{m}$ waveband and (b) $1.55\text{-}\mu\text{m}$ waveband. (From Ref [14])	98
Figure 3.10	Schematic diagram of athermal AWG with silicone resin-filled triangular groove. (Adapted from Ref [15])	100
Figure 3.11	Temperature-dependent transmission spectrum of Channel 4 over the temperature range of $0\text{--}85\text{ }^{\circ}\text{C}$ for (a) conventional silica-based AWG and (b) athermal AWG with silicon resin-filled triangular groove. (From Ref [16])	100
Figure 3.12	Temperature-dependent wavelength shift of Channel 4 in the temperature range of $0\text{--}85\text{ }^{\circ}\text{C}$. (From Ref [16])	101
Figure 3.13	Reduction of excess loss by replacing triangular groove of wider width with several grooves of smaller widths. (From Ref [17])	101
Figure 3.14	Schematic diagram of modified low-loss groove and array structure for a $1.5\%\text{-}\Delta$ athermal AWG. (From Ref [21])	102
Figure 3.15	Schematic diagram of silicon resin-filled trenches in the slab region of $1.5\%\text{-}\Delta$ athermal AWG. (From Ref [20])	102
Figure 3.16	Schematic diagram of silicon resin-filled trenches with spot size converters based on segmented core in the slab region of $2.5\%\text{-}\Delta$ athermal AWG. (From Ref [19])	103
Figure 3.17	(a) Cross-sectional view of silica/polymer hybrid waveguide; (b) comparison of measured TE/TM polarization shift of the central wavelength, Channel 9, with polymer and silica overcladding; (c) measured temperature-dependent wavelength shift of Channel 9 with polymer and silica cladding. (Adapted from Ref [22])	104
Figure 3.18	All-polymer 8×8 AWG with 200 GHz channel spacing: (a) measured spectra; (b) measured TE/TM polarization shift of Channel 4; (c) measured temperature-dependent transmission spectrum of Channel 4 for the temperature range of $25\text{--}65\text{ }^{\circ}\text{C}$. (Adapted from Ref [23])	105

Figure 3.19	Schematic diagram of an athermal AWG with temperature compensating plate. (From Ref [24])	105
Figure 3.20	Optical spectra of the athermal AWG with temperature compensating plate shown in Fig. 3.19. (From Ref [24])	106
Figure 3.21	Schematic diagram of an athermal AWG chip with temperature-compensating rod. (From Ref [25])	106
Figure 3.22	(a) Optical spectra in C- and L-bands of athermal AWG using temperature-compensating rod; (b) temperature-dependent wavelength shift of four channels in the C-band from -30°C to $+70^{\circ}\text{C}$. (Adapted from Ref [25])	107
Figure 3.23	Schematic diagram of AWG with bimetal plate. (From Ref [26])	108
Figure 3.24	Center wavelength of AWG as a function of temperature. (From Ref [26])	109
Figure 3.25	Field assembly (FA) connector: (a) structure of plug and socket; (b) in optical cabinet at customer premises. (From Refs [32] and [33])	110
Figure 3.26	(a) Connection loss trials and (b) return loss trials. (From Ref [32])	111
Figure 3.27	Bendable SC connector. (From Ref [33])	111
Figure 3.28	Cross-sectional view of angled physical contact (APC) connector. The 8-degree fiber end face directs reflected light into the cladding. (From Ref [34])	112
Figure 3.29	(a) Bend loss characteristics of bend resistant fiber; (b) comparison of conventional optical fiber with minimum bending radius of 30 mm and bend-resistant with minimum bending radius of 15 mm. (From Ref [32])	113
Figure 3.30	(a) Typical spectral attenuation of PureAccess-Ultra; (b) bending loss properties as a function of wavelength. (From Ref [37])	114
Figure 3.31	Schematic diagram of optical curl cord. (From Ref [39])	115
Figure 3.32	Connection of laptop terminal to optical outlet in the wall using optical curl cord. (From Ref [39])	115
Figure 3.33	Cross section and refractive index profile of hole-assisted fiber. (From Ref [38])	116
Figure 3.34	Bending loss characteristics of hole-assisted fibers: (a) calculated bending loss performance as a function of normalized hole distance; (b) wavelength dependence of measured bending loss. (From Ref [38])	117

Figure 3.35	(a) Calculated and experimental mode field diameter mismatch as a function of hole arrangement; (b) splice loss induced by MFD mismatch as a function of refractive index difference between N_{hole} and N_{clad} . (From Ref [38])	118
Figure 3.36	Comparison of three GI-POFs with differing core diameter and numerical aperture (NA): (a) refractive index profile; and (b) bending loss as a function of radius. (From Ref [47])	120
Figure 3.37	(a) Core diameter and (b) NA dependence loss at bending radius of 5 mm. (From Ref [47])	121
Figure 3.38	(a) Bending loss of GI POF with a core diameter = $200\ \mu\text{m}$ and NA = 0.24; (b) optimum waveguide parameters of GI POF to suppress the bending loss. (From Ref [47])	122
Figure 3.39	Schematic diagram of an index-guided Fabry–Perot laser diode. Optical spectra showing multiple longitudinal lasing modes.	123
Figure 3.40	Schematic diagram of a distributed feedback laser. Optical spectrum showing excellent single-mode behavior.	124
Figure 3.41	Schematic diagram of a vertical-cavity surface-emitting laser (VCSEL) with circular output beam.	125
Figure 3.42	WDM-PON using directly modulated OIL-VCSELs as ONU transmitters. Each slave VCSEL, located at the ONU is injection-locked by modulated downstream signal transmitted from a master DFB laser located at the CO. (From Ref [56])	126
Figure 3.43	Upstream BER curves for different values of (a) upstream signals to Rayleigh backscattering ratio (SRR) at a constant downstream extinction ratio (ER) = 4.5 dB; (b) downstream ER at a constant SRR = 13.4 dB.	127
Figure 3.44	Received optical power at BER = 10^{-9} as a function of downstream extinction ratio. Solid line: bidirectional 25-km transmission with Rayleigh backscattering effects. Dash line: unidirectional back-to-back transmission.	128
Figure 3.45	Schematic diagram of WDM-PON with broadband optical source (LED) in ONU. (From Ref [62])	130

Figure 3.46	Experimental setup of WDM-PON with centralized supercontinuum broadband light source. (From Ref [67])	131
Figure 3.47	Schematic diagram of colorless bidirectional (BiDi) transceivers based on FP-LDs injection-locked by the spectrally sliced light from a broadband super-luminescent LED (SLED). (From Ref [72])	132
Figure 3.48	Optical spectra of total injection light and spectrum-sliced injection lights measured at the input and output ports of the (a) remote node AWG and (b) central office AWG. (From Ref [72])	133
Figure 3.49	Schematic diagram of colorless reflective semiconductor optical amplifier (RSOA) wavelength seeded by spectrally sliced light from a broadband (SLED). (From Ref [81])	134
Figure 3.50	Monolithic indium phosphide-based RSOA features a curved waveguide architecture. (From Ref [82])	135
Figure 3.51	WDM-PON with self-injection-locked Fabry-Perot laser diodes (FP-LDs). (From Ref [81])	136
Figure 3.52	Optical spectra of self-injection-locked FP-LD. (From Ref [81])	136
Figure 3.53	Schematic diagram of WDM-PON with self-seeding reflective SOAs. (From Ref [85])	137
Figure 3.54	Overlapped optical spectra of 1.25 Gbps self-seeded upstream channels. (From Ref [85])	138
Figure 3.55	RITE-net architecture. The CW portion of each downstream packet is remodulated with upstream data at the optical network unit. (From Ref [86])	138
Figure 3.56	WDM-PON using reflective semiconductor optical amplifiers to amplify and remodulate downstream wavelengths carrying downstream signals (ASK format) for upstream transmission. (From Ref [90])	139
Figure 3.57	Optical spectrum of adiabatic-chirped DFB laser source directly modulated with 1.25 Gbps NRZ signal. Superimposed on the spectrum is the passband characteristic of negatively detuned (-18.7 GHz) demultiplexer. (From Ref [92])	140
Figure 3.58	Wavelength reuse scheme for WDM-PON using multichannel fiber Bragg grating to filter out downstream carriers for remodulation with upstream data. (From Ref [93])	141

Figure 4.1	The general PON network architecture for the FTTx scenario.	152
Figure 4.2	Physical layer burst-mode timing definition. T_{ON} – Tx turn-on time; T_{OFF} – Tx turn-off time; T_{DSR} – Rx dynamic sensitivity recovery time; T_{LR} – Rx level recovery time; T_{CR} – Rx clock recovery time; T_{DL} – Rx delimiter time.	157
Figure 4.3	Various PON diplexer and triplexer transceivers for optical access systems.	161
Figure 4.4	Feature function blocks of optical transceivers showing both downstream and upstream directions. In the upstream direction, an ONU transmitter consists of a burst-mode laser driver (BM-LD), and an F-P laser in the form of transmit optical subassembly (TOSA); the OLT receiver consists of a PIN or avalanche photodiode (PIN or APD), BM-trans-impedance (BM-TIA) ROSA (receive optical subassembly), a limiting post-amplifier (post-amp) and a burst-mode clock/data recovery (BM-CDR) unit.	162
Figure 4.5	Typical L-I curves of (a) DFB-LD and (b) F-P LD.	164
Figure 4.6	APD V-I curve and multiplication factor.	165
Figure 4.7	Schematics structures of TO-CAN packaging for DFB (a) and APD (b). Their photographs are shown on the right.	166
Figure 4.8	Transmission spectrum characteristic (left) and photograph (right) of the WDM filter formed on a fiber facet [29]. The two curves represent two different light polarizations.	166
Figure 4.9	BOSA schematics for three wavelengths based on thin-film technology.	168
Figure 4.10	The BOSA in TO-CAN package with driving circuit [32].	169
Figure 4.11	Optical circuit configurations with external filters.	170
Figure 4.12	The feasibility of grating assisted WDM filter on a PLC platform (top) and conceptual schematic (bottom) of a triplexer using this structure [43].	171
Figure 4.13	Bidirectional ONU diplexer transceiver module.	173
Figure 4.14	Bidirectional ONU triplexer transceiver module.	173
Figure 4.15	Data formats in digital communication: (a) continuous-mode data, (b) burst-mode data, (c) burst packet data [47].	175

Figure 4.16	Temperature characteristics of a typical F-P laser as L-I curves.	176
Figure 4.17	Block diagram of a typical burst-mode laser driver IC [49].	177
Figure 4.18	Comparison of (a) continuous and (b) burst-mode laser driver stage.	178
Figure 4.19	Block diagrams of two typical APC circuits.	179
Figure 4.20	Optical and timing performance of an EPON BM-Tx: (top left) Optical eye diagram using 4th-order Thompson filter at 1.25 Gbps; numbers inside box are GbE eye-mask margin. (Bottom left) Optical bursty signal with Laser bias on/off. The measured laser burst-on and burst-off times are shown on the right side [22].	180
Figure 4.21	Optical eye diagrams at -40°C and 80°C case temperature with optical power above 0 dBm and ER above 10 dB. The numbers inside box are GbE eye-mask margin.	181
Figure 4.22	Feed-forward and feedback implementations of optical burst-mode receivers.	182
Figure 4.23	Block diagram of a burst-mode preamplifier IC employing ATC (left) and the response of ATC circuit (right) [56].	183
Figure 4.24	The comparison of (a) a conventional AGC and (b) a cell-AGC for burst-mode inputs with low extinction ratio [60].	184
Figure 4.25	Configuration and operation principles of cell-AGC based preamplifier IC.	185
Figure 4.26	Comparison of AC-coupled (left) versus DC-coupled (right) burst-mode receivers.	186
Figure 4.27	An example of 1.25 Gbps BM APD/TIA output eye diagram (left) and settling time measurements (right) [22].	187
Figure 4.28	Examining temperature error at different ADC resolutions. The y-axis shows the absolute value of the maximum error. The overall error for the temperature monitoring is $\pm 1^{\circ}\text{C}$. The blue, pink, and green lines represent the 8-, 10-, and 12-bit ADCs, respectively. The solid lines represent the cases in which the accuracy level of both the temperature sensor and the voltage reference is within $\pm 1\%$, and the dashed lines represent a $\pm 0.5\%$ accuracy level. The red solid line is a 10-bit ADC without oversampling [70].	189

Figure 4.29	A Laser output power and monitoring current versus driving current.	191
Figure 4.30	A tunable OTDR example for in-service monitoring of the fiber fault in WDM-PON [74].	192
Figure 4.31	Fiber fault detection results for fault locations at (a) 3 km, (b) 3.4 km, (c) 4 km, and (d) 5.2 km from the remote node using the setup from Fig. 4.30.	194
Figure 4.32	Embedded OTDR into ONU burst-mode transmitter. OTDR analog front-end bandwidth is limited to 5 MHz [76].	194
Figure 4.33	ONU block diagram with OTDR functionality integrated [77].	195
Figure 4.34	Typical burst-mode test setup configuration consisting of two ONUs. A weak packet from BM-Tx as ONU#1 followed by a strong packet from commercial SFF module Tx as ONU#2 emulates the worst-case condition [22].	198
Figure 4.35	A typical G-PON upstream burst-mode test pattern when strong packets from BM-Tx as ONU#1 are followed by the weak packets from ONU#2. The overhead guard time consists of the mandatory 32 bits, preamble 44 bits, and delimiter time 16–20 bits.	199
Figure 4.36	Typical measurements of burst-mode BER (top) and sensitivity penalty (bottom) performed for a DC-coupled G-PON OLT Rx at 1.244 Gbps.	200
Figure 4.37	1.25-Gbps G-PON uplink performance with PLM.	201
Figure 4.38	(a) Measured continuous-mode (P2P) versus burst-mode BER. (b) Input and output for burst-mode receiver.	203
Figure 4.39	Burst-mode BER curves for the weak packet as a function of the power levels of the strong packet at 1.25 Gbps, indicating the degradation of OLT Rx sensitivity due to the influence of the strong packet.	204
Figure 4.40	(a) Impact of CATV signal on BER of the digital receiver. (b) Impact of digital signal cross talk on the CNR of CATV receiver.	206
Figure 5.1	Time division multiple access.	216
Figure 5.2	Ranging window.	217
Figure 5.3	G-PON ranging phase 1: serial number process.	219
Figure 5.4	GPON ranging phase 2: delay measurements.	220
Figure 5.5	Dynamic bandwidth allocation.	222
Figure 5.6	An example network configuration which offers Layer-2 link services to ISPs.	224

Figure 5.7	The principle of Fair Queuing.	226
Figure 5.8	Operation of limited service IPACT: (a) when only ONU#3 has upstream traffic; and (b) when all ONUs have upstream traffic. Here, R1, R2, and R3 represent request messages from each ONU respectively; data#3 represents user data transmitted from ONU#3. G3 represents grant for ONU#3. In (a), the values of R1 and R2 are equal to 0 and the value of R3 indicates amount of upstream user data stored in ONU#3.	230
Figure 5.9	Deficit round-robin (DRR) scheduling.	234
Figure 5.10	Maintaining short round-robin cycle using multiple queue request.	235
Figure 5.11	An example with two types of requests.	235
Figure 5.12	An IEEE802.3ah REPORT frame with multiple requests.	236
Figure 5.13	Burst allocation example of DRR using multiple queue report set.	237
Figure 5.14	Comparison of bandwidth efficiency (E_{max}) among the three DBAs covered in this chapter. Here we have chosen the number of ONU $N = 32$, Burst overhead $= 1.4\mu\text{sec}$, Max RTD $= 100\mu\text{sec}$, $w_i = w$, $Th_i = w/N$, OLT processing time $= 16\mu\text{sec}$, and ONU processing time $= 16\mu\text{sec}$.	241
Figure 6.1	Protection switching architectures suggested by ITU-T G.983.1.	249
Figure 6.2	A 1:N protection scheme at OLT [14]. LT: Line Terminal.	250
Figure 6.3	A PON architecture with protection of distribution fibers by interconnecting ONUs with protection switching [17]. OSW: optical switch, FBG: fiber Bragg gratings, λ_d : downstream wavelength, λ_u : upstream wavelength.	251
Figure 6.4	A PON architecture with protection of both feeder and distribution fibers by an additional loopback distribution fiber with protection switching [18]. λ_d : downstream wavelength, λ_u : upstream wavelength.	252
Figure 6.5	Protection of feeder fibers in two PONs using CWDM technology [19]. OSW: optical switch, λ_d : downstream wavelength, λ_u : upstream wavelength.	252
Figure 6.6	An example of a four-fiber shared rings in (a) normal operation; (b) span switching; and (c) ring switching [25].	254

- Figure 6.7** A modified star-ring PON with protection capability [26]. Inset shows the structure of the RN to illustrate the protection mode. OS: optical switch. 255
- Figure 6.8** The structure of (a) the OLT and (b) RN of a WDM-PON with duplicated fiber feeders for protection [27]. AN: access node, CN: central node, OSC: optical supervisory channel, PD: photodiode, OSW: optical switch. 256
- Figure 6.9** Self-protected network architecture for WDM-PON. LD1–4: laser diode; PD1–4: PIN photodiode; WC: WDM coupler; M1&M2: optical power monitors; $\{A_i, C_i\}$ for $i \in \{1, \dots, N\}$: upstream wavelengths; $\{B_i, D_i\}$ for $i \in \{1, \dots, N\}$: downstream wavelengths. Inset shows the spectral response of one of the output ports of the AWG. FSR: free-spectral range of the AWG [28]. 258
- Figure 6.10** (a) A WDM-PON survivable architecture with eight ONUs and centralized protection switching control; (b) OLT configuration under normal operation; (c) wavelength assignment plan. B/R: blue/red filter; OC: 3-dB fiber coupler; LD: laser diode; PD: photodiode. Note: FSR1 stands for free-spectral range of the $N \times 2$ ($N = 8$) AWG at the OLT while FSR2 stands for that of both AWG1 and AWG2 at the RN. The wavelengths quoted in boxes are the working upstream wavelengths. The wavelengths in blue band are underlined but those in red band are not [31]. 259
- Figure 6.11** A WDM-PON architecture with self-protection capability against both feeder fiber and distribution fiber failures [32]. WC: wavelength coupler, B/R: blue/red filter, OS: optical switch, M: power monitoring modules. 260
- Figure 6.12** (a) A single-fiber CWDM optical access ring network; (b) & (c) the structure of AN2 in (b) normal state and (c) protection state when there was a fiber cut between AN2 and AN3 [45]. AN: access node, Tx: transmitter, Rx: receiver. 262
- Figure 6.13** (a) A protected optical star-shaped ring network; (b) lightpath diagram, dotted lines were the designated protection paths; (c) the protection lightpath was adopted when node 1 failed [47]. FBG: fiber Bragg gratings. 263
- Figure 7.1** The architecture of a passive optical-access network. 268

Figure 7.2	Points where the test required for a WDM, point-to-multipoint, and bidirectional PON.	272
Figure 7.3	Three layers of optical performance monitoring: transport monitoring, signal quality monitoring, and protocol monitoring.	279
Figure 7.4	Example on the detection and localization of fiber failures in a bidirectional WDM-PON [15].	283
Figure 7.5	Fiber-link loss monitoring example in a bidirectional WDM-PON using ASE-injected FP-LD [17].	284
Figure 7.6	Schematic of an OWDR-embedded FTTH network from OLT to ONT [18].	285
Figure 7.7	(a) Undermined noise level: different noise on adjacent signal channels; (b) “Missing” noise between channels: optical filters or MUX/DEMUX may remove the out of band noise.	287
Figure 7.8	Operating principle of the polarization technique: the polarized noise (i.e. half of the total noises) can be measured by using the second linear polarizer, which is aligned to be orthogonal to the signal’s polarization [25].	287
Figure 7.9	RF pilot tone added to the channel bandwidth as the signal quality/degradation monitor.	288
Figure 7.10	(a) Typical measured data for the logarithm of the BER versus the decision threshold [37]; (b) the BER as a function of the received optical SNR [41].	290
Figure 7.11	OCDM-based PON-monitoring system where every network leg is assigned an encoder. One tunable decoder is employed at the CO [42].	291
Figure 7.12	System configuration of optical fiber line testing system using a 1650-nm testing window [43].	292
Figure 7.13	Conceptual diagram for monitoring chromatic dispersion using optical vestigial-sideband (VSB) filtering: the recovered bits from either part of the spectrum arrive at slightly different times depending on the chromatic dispersion [50].	294
Figure 7.14	The use of the degree of polarization (DOP) to monitor the effects of PMD: (a) DOP measurements as a function of instantaneous DGD. Note that the DOP is pulse-width-dependent [52]; and (b) measured DOP for a 40-Gbit/s RZ signal with concatenation of 6-ps and 4-ps DGD sections [58]. Note that higher-orders	

	of PMD decrease the signal’s maximum DOP at the receiver to less than unity.	295
Figure A1.1	Generic physical configuration of the optical distribution network (reproduced from Figure 5/G.983.1).	301
Figure A2.1	Gate frame format.	311
Figure A2.2	Report frame format.	312
Figure A2.3	Register request frame format.	312
Figure A2.4	Register frame format.	313
Figure A2.5	Register acknowledgment frame format.	313

List of Tables

Table 1.1	Summary of different DSL technology performances	4
Table 1.2	Summary of DOCIS data rates	6
Table 1.3	Bandwidth requirements for different IP services	13
Table 2.1	APON downstream/upstream bit-rate combinations	38
Table 2.2	Selected properties of IEEE802.3ah EPON transmitters	57
Table 2.3	Selected properties of IEEE 802.3ah receiver characteristics	58
Table 2.4	G-PON and EPON comparison	69
Table 4.1	PON power budgets	154
Table 4.2	ITU-T G.983.3 BPON standards	156
Table 4.3	Physical-layer requirements of ITU-T G-PON and IEEE EPON standards	157
Table 4.4	G-PON and EPON burst-mode timing comparison	158
Table 4.5	Key PMD parameters of G-PON class B 1.244 Gbps upstream [10, 20]	159
Table 4.6	Key PMD parameters of IEEE 802.3ah EPON 20-km 1.25 Gbps upstream [9, 22]	160
Table 4.7	State-of-the-art G-PON transceiver performance parameters for the upstream link at 1.244 Gbps, in comparison with the ITU-T G.984.2 specifications [10]	201
Table 4.8	A state-of-the-art EPON transceiver uplink performance summary in comparison with the IEEE 802.3ah standard	205
Table A1.1	G.984.2—Physical medium dependant layer parameters of ODN (reproduced from Table 2a/G.984.2)	302
Table A1.2	G.984.2—Optical interface parameters of 1244 Mbit/s downstream direction (reproduced from Table 2b/G.984.2)	303
Table A1.3	G.984.2—Optical interface parameters of 2488 Mbit/s downstream direction (reproduced from Table 2c/G.984.2)	305
Table A1.4	G.984.2—Optical interface parameters of 1244 Mbit/s upstream direction (reproduced from Table 2f-1/G.984.2)	307
Table A1.5	G.984.2—Optical interface parameters of 1244 Mbit/s upstream direction using power-levelling mechanism at ONU Transmitter (reproduced from Table 2f-2/G.984.2)	309