

Cécile Grèzes

Towards a Spin-Ensemble Quantum Memory for Superconducting Qubits

Design and Implementation of the Write,
Read and Reset Steps

Doctoral Thesis accepted by
the University of Paris VI, France

Contents

1	Introduction	1
1.1	Rationale for the Hybrid Way	1
1.2	Spin Ensemble Quantum Memory Principle	4
1.3	Storing a Qubit State in a Spin Ensemble (Write)	6
1.4	Retrieving Few-Photon Fields Stored in a Spin Ensemble (Read)	10
1.5	NV Clock Transitions for Long Coherent Storage	13
1.6	Towards an Operational Quantum Memory	14
	References	16
2	Background	19
2.1	Superconducting Circuits and Microwave Engineering	19
2.1.1	Superconducting Resonators	19
2.1.2	Josephson Junction Based Circuits	29
2.1.3	Circuit Quantum Electrodynamics	39
2.2	NV Center Spins in Diamond	45
2.2.1	Structure	45
2.2.2	The NV Center Spin Qubit	46
2.2.3	Coherence Times	51
2.3	Coupling Ensembles of NV Center Spins to Superconducting Circuits	53
2.3.1	Single Spin-Resonator Coupling	53
2.3.2	Spin Ensemble-Resonator Coupling: Collective Effects	54
2.3.3	The Resonator-Spins System in the Low-Excitation Regime	65
2.3.4	The Resonator-Spins System Under Strong Drive Powers	74
	References	75

3	Proposal: A Spin Ensemble Quantum Memory for Superconducting Qubits	79
3.1	Spin-Based Quantum Memory	79
3.1.1	Motivations	79
3.1.2	Spin Ensemble Quantum Memory: Principles	80
3.2	Spin Ensemble Quantum Memory Protocol	82
3.2.1	The Write Step: Storage of N Quantum States $ \psi_1\rangle \dots \psi_n\rangle$	82
3.2.2	The Read Step: On-Demand Retrieval of $ \psi_i\rangle$	83
3.2.3	The Full Quantum Memory Protocol	86
3.3	Simulations	87
	References	89
4	Experiment 1 (Write): Coherent Storage of Qubit States into a Spin Ensemble	93
4.1	State of the Art and Principle of the Experiment	93
4.1.1	State of the Art	93
4.1.2	Strong Coupling of NVs to a Superconducting Resonator	94
4.1.3	Principle of the Experiment	96
4.2	Experimental Realization	98
4.2.1	The Hybrid Quantum Circuit	98
4.2.2	Measurement Setup	104
4.3	Operating the Hybrid Quantum Circuit	110
4.3.1	Superconducting Circuit Characterization	110
4.3.2	Transferring Qubit States to the Bus Resonator	118
4.3.3	Coupling the NV Spin Ensemble to the Bus Resonator	120
4.4	Storage of Qubit States into a NV Spin Ensemble	122
4.4.1	Storing a Single Photon from the Qubit into the Spin Ensemble	122
4.4.2	Storing a Coherent Superposition from the Qubit to the Spin Ensemble	126
4.4.3	Entanglement Between the Spin Ensemble and the Resonator	129
4.5	Conclusions on Experiment 1: The Write Step	131
	References	132
5	Experiment 2 (Read): Multimode Retrieval of Few Photon Fields from a Spin Ensemble	133
5.1	Principle of the Experiment	133
5.2	Experimental Realization	135
5.2.1	The Hybrid Quantum Circuit	135
5.2.2	Measurement Setup	139

5.3	Spectroscopy of the Resonator-Spins System	145
5.3.1	Characterization of the Resonator.	146
5.3.2	System Spectroscopy at Zero-Magnetic Field.	147
5.4	Active Reset of the Spins	150
5.4.1	Effect of Light Irradiation on the Superconducting Resonator	150
5.4.2	Continuous Irradiation: Dependence of the Spin Polarization on the Optical Power	156
5.4.3	Pulsed Irradiation: Active Spin Polarization.	160
5.4.4	Spin Relaxation Time Measurement	165
5.5	Multimode Retrieval of Few Photon Fields Stored in a Spin Ensemble	166
5.5.1	Applying Hahn Echoes to the Spin Ensemble	166
5.5.2	Retrieval of Few-Photon Pulses Stored in the Spin Ensemble	174
5.6	NV Clock Transitions for Long Coherent Storage	181
5.6.1	Atomic Clock Transitions in NV Centers in Diamond . . .	181
5.6.2	Full System Spectroscopy	182
5.6.3	Dependence of the Echo Coherence Time on the Magnetic Field	185
5.6.4	Advanced Analysis: Spin Classes Contributions to the Echo Decay	189
5.7	Conclusion on Experiment 2: The Read Step.	195
	References	197
6	Towards an Operational Quantum Memory	199
6.1	Reaching Efficient Memory Operations.	199
6.1.1	Storage and Retrieval of Photon Fields at the Single Photon Level with Improved Efficiencies	199
6.1.2	Reaching the Operational Level	205
6.2	Running the Full Quantum Memory Protocol	207
6.2.1	Step 1/2: Realization of a Frequency Tunable Resonator Compatible with Refocusing Pulse Applications	207
6.2.2	Realizing a Hybrid Circuit Able to Run the Full Memory Protocol.	215
	References	218
7	Conclusions and Perspectives	219
	References	221

Appendix A: Fabrication 223

Appendix B: NV Center Distribution 225

Curriculum Vitae 229