

Table of Contents

1 **Introduction 1**

2 **General code features 3**

2.1 Code basis 3

2.2 Major code versions 3

2.3 Differences between TOUGH2 and TOUGH2-MP 5

2.4 Deviations from TOUGH2 and TOUGH2-MP defaults 6

2.4.1 Unlimited number of materials (only TOUGH2-GRS)..... 6

2.4.2 Unlimited number of time steps..... 6

2.4.3 Automatic Leverett scaling disabled..... 6

2.4.4 Extended printouts 7

2.4.5 Conservation of floating point precision (only TOUGH2-GRS) 7

2.4.6 Enforced solution of linear equations 7

2.5 Modules and physical processes 8

2.6 Handling porosity changes 10

2.7 Handling permeability changes 12

3 **New flow and transport features..... 13**

3.1 Check valve boundary (IRP=9 in combination with an upstream
weighting of mobilities)..... 13

3.2 Simulated vertical pressure gradient (ICP=9 with IRP=1)..... 13

4 **CNTRL: Simulation controls 17**

4.1 Termination controls..... 17

4.1.1 Do not exit on equilibrium (obsolete)..... 17

4.1.2 Minimum time step width..... 17

4.2 Time step controls 18

4.2.1	Incrementing step widths	18
4.2.2	Avoiding convergence failures	18
4.2.3	Avoiding small time steps before printout times	18
4.2.4	Avoiding large changes in gas generation	19
4.3	Output controls	19
4.3.1	Precision of time series printouts	19
4.3.2	Reducing the amount of time series printouts	19
4.4	Input data	20
5	COMP: Convergence and compaction	21
5.1	Physical models	21
5.1.1	Change of cavity volume and porosity	21
5.1.2	Compaction rates	22
5.2	Note on the compaction of saturated media	24
5.3	Input data	24
6	CORFL	27
6.1	Implementation	27
6.2	Source and sink calculation	28
6.3	Degree of corrosion	29
6.4	Permeability change	30
6.5	Input data	31
7	CORRO: Gas production due to iron corrosion	33
7.1	Water consumption	33
7.2	Gas component	34
7.3	Gas generation rates	37
7.4	Input data	40

8	DEGRA: Time-dependent permeability changes.....	43
8.1	Model and implementation	43
8.2	Input data	43
9	DOFT	45
10	FISS: Gas pathway dilation	47
10.1	Pressure thresholds and softening models	47
10.2	Fissure porosity models	48
10.3	Permeability models	49
10.4	Input data	51
11	GCOMP: Primary non-condensable gas component.....	53
11.1	Absolute molecular weight	53
11.2	Specific enthalpy	53
11.3	Inverse Henry constant	54
11.4	Gas phase viscosity	54
11.5	Input data	56
12	PRLIM: Gas pressure limitation	57
12.1	Model and implementation	57
12.2	Input data	58
13	PTIME: High-precision printout times	59
14	RANGE: Limiting primary variables	61
14.1	Limiting brine mass fraction	61
14.2	Constant brine mass fraction	62

14.3	Clipping gas saturation and reducing vapour pressure	62
14.4	Input data	64
15	RELA: permeability and capillary pressure functions.....	65
15.1	Porosity-permeability relationships	65
15.2	Change of capillary pressures.....	65
15.3	Temperature-dependent capillary pressures	66
15.4	Input data	66
16	RN	69
16.1	Links to standard TOUGH2.....	69
16.2	Time stepping and performance	69
16.3	Simulation controls.....	71
16.4	Decay and adsorption of Nuclides	71
16.5	Anion exclusion	72
16.6	Extended mobilization models	75
16.6.1	New commands	75
16.6.2	Canister failure models	76
16.6.3	Bond models	79
16.6.4	Implementation.....	79
16.7	Input data	81
17	Output	83
17.1	Global printouts for elements (ELE_MAIN)	83
17.2	Global printouts for connections (CON_MAIN)	86
17.3	Time series for elements (FOFT).....	88
17.4	Time series for connections (COFT)	90
17.5	Time series for sinks and sources (GOFT)	91

17.6 Time series for domains (DOFT)..... 92

References..... 93

List of Figures 99

List of Tables 101

Acknowledgements 103